



+ CONNECTORS
RF CONNECTORS



✓ Active

TE CONNECTIVITY (TE)
SMA STR JACK FOR PCB MOUNT
Subminiature Coax | SAM , SMA

1470510-1
TE Internal Number: 1470510-1

- EU RoHS Compliant
- EU ELV Compliant
- Connector Interface SMA
- Connector Style Jack
- Mated Outer Diameter (Approximate) 6.35 mm [.25 in]
- Impedance (Ω) 50
- Operating Frequency (GHz) 6

↓ 3D PDF

DOCUMENTATION

Product Drawings
SMA STR JACK FOR PCB
TIF
English

CAD Files

3D PDF
PDF
3D

Customer View Model
2D_DXF.ZIP
English

Customer View Model
3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

- Connector Interface SMA
- Connector Style Jack
- Connector & Contact Terminates To Printed Circuit Board

Configuration Features

- PCB Mounting Orientation Vertical

Electrical Characteristics

- Impedance (Ω) 50

Body Features

- Body Material Brass
- Body Plating Material Gold

Contact Features

- Connector Product Type Connector Assembly
- RF Connector Contact Configuration Not Captivated

Dimensions

- Mated Outer Diameter (Approximate) 6.35 mm [.25 in]
- Length 13.97 mm [.55 in]

Operation/Application

- Operating Frequency (GHz) 6

Packaging Features

- Packaging Method Bag
- Packaging Quantity 100

Other

- Dielectric Material PTFE

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
