

+ RELAYS, CONTACTORS & SWITCHES

DC



✓ Active

# TE CONNECTIVITY (TE) LEV200H4ANA, RELAY SPST-NO

Kilovac | LEV200

LEV200H4ANA

TE Internal Number: 6-1618390-8

## **EU RoHS Compliant EU ELV Compliant**

Contact Arrangement 1 Form X, SPST-NO DM

Contact Current Rating (A) 500

Coil Voltage (Max) (VDC) 12

Coil Voltage Rating (VDC) 12

**Coil Termination** Wire



**★** 3D PDF

#### **DOCUMENTATION**

**CAD Files** 

3D PDF

PDF

**3D** 

### **Customer View Model**

2D\_DXF.ZIP

**English** 

### **Customer View Model**

3D\_IGS.ZIP

**English** 

## **Customer View Model**

3D\_STP.ZIP

**English** 

Catalog Pages/Data Sheets	
5-1773450-5_sec7_LEV200	
PDF	
English	
Agency Approvals	
UL	
CONTACTOR, MODELS EV200, LEV200, LEV100 AND EVC135 REPORT	
PDF	
English	
FEATURES	+
Please review product documents or contact us for the latest agency approval information.	
Product Type Features	
Terminal Configuration 10-32 Stud	
Contactor Type Sealed	
Product Category Electromechanical Relays	
Product Type Contactor	
Product Classification Relays - Contactors	
Configuration Features	
Auxiliary Switch Contact Arrangement None	
Electrical Characteristics	
Coil Voltage (Max) (VDC) 12	
Coil Voltage Rating (VDC) 12	
Actuating System DC	
Contact Features	
Contact Arrangement 1 Form X, SPST-NO DM	
Contact Arrangement 17 offit X, 51 51-100 DW	
Number of Poles 1	
Termination Features	
Coil Termination Wire	
Con remination wife	
Mechanical Attachment	
Mounting Type Bottom	
Dimensions	
Coil Wire Length 390 mm [15.3 in]	

Packaging Features
Packaging Method Individual

Other
Torque (in-lbs) 80 – 100

PRODUCT COMPLIANCE

Statement of Compliance
Statement of Compliance
PDF