# DEWC611MT03000001000 ACTIVE



TE Internal #: DFC611T03000001000

Cable-to-Panel, 4 Position, Wire & Cable, Power, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, Standard Circular

Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Panel

Connector Mounting Type: Panel Mount

Number of Positions: 4

Sealable: No

Connector & Contact Terminates To: Wire & Cable

### **Features**

## Product Type Features

Product Type Connector Assembly  Connector System Cable-to-Panel  Sealable No  Connector & Contact Terminates To Wire & Cable  Circular Connector Type Receptacle  Shell Type Metal  Configuration Features  Number of Positions 4  Number of Power Positions 4  Number of Signal Positions 0  Contacts Preloaded Yes  Electrical Characteristics		
Sealable No  Connector & Contact Terminates To Wire & Cable  Circular Connector Type Receptacle Shell Type Metal  Configuration Features  Number of Positions 4  Number of Power Positions 4  Number of Signal Positions 0  Contacts Preloaded Yes	Product Type	Connector Assembly
Connector & Contact Terminates To  Circular Connector Type  Receptacle  Shell Type  Metal  Configuration Features  Number of Positions  Aunuber of Power Positions  Number of Signal Positions  Contacts Preloaded  Wire & Cable  Receptacle  Metal  Metal  O  State of Power Positions  4  Number of Power Positions  O  Contacts Preloaded  Yes	Connector System	Cable-to-Panel
Circular Connector Type Receptacle Shell Type Metal  Configuration Features  Number of Positions 4  Number of Power Positions 4  Number of Signal Positions 0  Contacts Preloaded Yes	Sealable	No
Shell Type Metal  Configuration Features  Number of Positions 4  Number of Power Positions 4  Number of Signal Positions 0  Contacts Preloaded Yes	Connector & Contact Terminates To	Wire & Cable
Configuration Features  Number of Positions 4  Number of Power Positions 4  Number of Signal Positions 0  Contacts Preloaded Yes	Circular Connector Type	Receptacle
Number of Positions4Number of Power Positions4Number of Signal Positions0Contacts PreloadedYes	Shell Type	Metal
Number of Power Positions4Number of Signal Positions0Contacts PreloadedYes	Configuration Features	
Number of Signal Positions0Contacts PreloadedYes	Number of Positions	4
Contacts Preloaded Yes	Number of Power Positions	4
	Number of Signal Positions	0
Electrical Characteristics	Contacts Preloaded	Yes
	Electrical Characteristics	

250 VAC, 630 VAC

# **Body Features**

Operating Voltage



Environmental Protection Type	Sealed
Environmental Protection	IP67
Shell Plating Material	Electrodeposited Nickel
Shell Base Material	Zinc Alloy
Circular Connector Insulation Material Type	PBT GF
Contact Features	
Contact Current Rating (Max)	150 A
Circular Connector Contact Type	Pin
Termination Features	
Termination Method to Wire & Cable	Screw
Mechanical Attachment	
Mating Retention Type	Screw
Flange	With
Mating Alignment	With
Panel Mount Feature	With
Panel Mount Feature Type	Flange with Mounting Holes
Connector Mounting Type	Panel Mount
Mating Retention	With
Housing Features	
Circular Connector Shell Size	58
Alignment Keyed	O°
Usage Conditions	
IP Water Sealing Level	IP67
Operating Temperature Range	-20 – 130 °C[-4 – 266 °F]
Operation/Application	
Durability Rating	500 Cycles
Circuit Application	Power
Shielded	Yes
Industry Standards	
UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL



## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Pb (3.5% in Component) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



# Customers Also Bought

09/17/2024 06:36AM | Page 3

Cable-to-Panel, 4 Position, Wire & Cable, Power, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, Standard Circular Connectors













TE Part #22-0190-035-000 940 FRONT PART, SPEEDTEC-R

TE Part #22-0363-031-000 923 RECEPTACLE,ANGLED, ROTATABLE,SPEEDTEC TE Part #22-0460-031-000 923 RECEPTACLE,ANGLED, ROTATABLE,SPEEDTEC

TE Part #2376243-1
RESOLVER,SCR308 STATOR TESTED
AND MARKED

TE Part #HEC402N00000300000
723 HTEC RECEPTACLE, SPEEDTEC

#### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_DFC611T03000001000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DFC611T03000001000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_DFC611T03000001000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

# Datasheets & Catalog Pages

DFC611T03000001000

English

fuer Datenblaetter, die online konfigurierbar sind

German

# DEWC611MT03000001000

Cable-to-Panel, 4 Position, Wire & Cable, Power, Panel Mount, Electrodeposited Nickel, Zinc Alloy, PBT GF, Standard Circular Connectors

