

Part Number: 1200680196

Product Description: Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male to 2 x 3-Pole Female, 22 AWG, 0.60m Length

Series Number: 120068

Status: Active

**Product Category:** Industrial Tees and

**Splitters** 

Engineering Number: 884A30K05M006



#### **Documents & Resources**

#### **Drawings**

Drawing 1200680196\_sd.pdf

### **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<u> </u>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Contains Lead per D(2022)4187-DC (10 June 2022)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

# **Part Details**

## General

Status	Active
Category	Industrial Tees and Splitters
Series	120068
Description	Micro-Change (M12) In-Line Splitter, 4 Pole, 1 x 4-Pole Male to 2 x 3-Pole Female, 22 AWG, 0.60m Length
IP Rating	IP67
Product Family	Brad Micro-Change (M12) Connectors
Product Name	Micro-Change (M12)
Туре	Splitter - In-line
UPC	78678883430

# Agency

CSA	LR6837
UL	E152210

## Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

## Physical

Color - Cable Jacket	Yellow
Drop Connector	N/A
Drop Gender	N/A
Keyway	Single
LED Indicator	No
Left Trunk Connector	Micro-Change (M12)
Left Trunk Gender	Male

Leg 1 Length	0.60m
Leg 2 Length	0.60m
Material - Cable Jacket	TPE
Material - Connector Body	TPE
Material - Coupling Nut	Nickel-plated Brass
Net Weight	85.000/g
Poles	3 Female/4 Male
Right Trunk Connector	Micro-Change (M12)
Right Trunk Gender	Female
Temperature Range - Operating	-30°C to +70°C

This document was generated on Sep 23, 2024