

Description

The SX65N04NF uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 4.5V. This device is suitable for use as a Battery protection or in other Switching application.

General Features

$V_{DS} = 40V$ $I_D = 65A$

$R_{DS(ON)} < 9m\Omega$ @ $V_{GS}=10V$



Application

Battery protection

Load switch

Uninterruptible power supply

PDFN5*6-8L



Absolute Maximum Ratings ($T_C=25^\circ C$ unless otherwise noted)

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	40	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D @ T_C=25^\circ C$	Continuous Drain Current, V_{GS} @ 10V ¹	65	A
$I_D @ T_C=100^\circ C$	Continuous Drain Current, V_{GS} @ 10V ¹	33	A
I_{DM}	Pulsed Drain Current ²	200	A
EAS	Single Pulse Avalanche Energy ³	81	mJ
I_{AS}	Avalanche Current	10	A
$P_D @ T_C=25^\circ C$	Total Power Dissipation ⁴	33.7	W
$P_D @ T_A=25^\circ C$	Total Power Dissipation ⁴	2	W
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ C$
$R_{\theta JA}$	Thermal Resistance Junction-Ambient ¹	3.7	$^\circ C/W$
$R_{\theta JC}$	Thermal Resistance Junction-Case ¹	2.1	$^\circ C/W$

Electrical Characteristics (T_J=25°C, unless otherwise noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BVDSS	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	40	---	---	V
△BVDSS/△T _J	BVDSS Temperature Coefficient	Reference to 25°C , I _D =1mA	---	0.028	---	V/°C
RDS(ON)	Static Drain-Source On-Resistance	V _{GS} =10V , I _D =30A	---	7.7	9.0	mΩ
		V _{GS} =4.5V , I _D =15A	---	9.4	12	
VGS(th)	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	1.2	1.6	2.5	V
△VGS(th)	VGS(th) Temperature Coefficient		---	-6.16	---	mV/°C
IDSS	Drain-Source Leakage Current	V _{DS} =40V , V _{GS} =0V , T _J =25°C	---	---	1	uA
		V _{DS} =40V , V _{GS} =0V , T _J =55°C	---	---	5	
IGSS	Gate-Source Leakage Current	V _{GS} =±20V , V _{DS} =0V	---	---	±100	nA
gfs	Forward Transconductance	V _{DS} =5V , I _D =30A	---	22	---	S
R _g	Gate Resistance	V _{DS} =0V , V _{GS} =0V , f=1MHz	---	1.7	3.4	Ω
Q _g	Total Gate Charge (4.5V)	V _{DS} =20V , V _{GS} =10V , I _D =25A	---	37	---	nC
Q _{gs}	Gate-Source Charge		---	6	---	
Q _{gd}	Gate-Drain Charge		---	7	---	
Td(on)	Turn-On Delay Time	V _{DD} =30V , V _{GS} =10V , R _G =1Ω I _D =25A	---	12	---	ns
T _r	Rise Time		---	12	---	
Td(off)	Turn-Off Delay Time		---	38	---	
T _f	Fall Time		---	9	---	
C _{iss}	Input Capacitance	V _{DS} =20V , V _{GS} =0V , f=1MHz	---	2400	---	pF
C _{oss}	Output Capacitance		---	192	---	
Crss	Reverse Transfer Capacitance		---	165	---	
I _s	Continuous Source Current ^{1,5}	V _G =V _D =0V , Force Current	---	---	50	A
ISM	Pulsed Source Current ^{2,5}		---	---	200	A
VSD	Diode Forward Voltage ²	V _{GS} =0V , I _s =1A , T _J =25°C	---	---	1.2	V
t _{rr}	Reverse Recovery Time	IF=30A , dI/dt=100A/μs , T _J =25°C	---	22	---	nS
Q _{rr}	Reverse Recovery Charge		---	11	---	nC

Note :

- 1、The data tested by surface mounted on a 1 inch 2 FR-4 board with 2OZ copper.
- 2、The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%
- 3、The EAS data shows Max. rating . The test condition is VDD=36V,VGS =10V,L=0.1mH,IAS =10A
- 4、The power dissipation is limited by 150°Cjunction temperature
- 5、The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation

Typical Characteristics




Figure1: Output Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 5: Gate Charge Characteristics




Figure 2: Typical Transfer Characteristics




Figure 4: Body Diode Characteristics




Figure 6: Capacitance Characteristics

Typical Characteristics




Figure 7: Normalized Breakdown Voltage vs. Junction Temperature




Figure 8: Normalized on Resistance vs. Junction Temperature




Figure 9: Maximum Safe Operating Area vs. Case Temperature




Figure 10: Maximum Continuous Drain Current





Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Case

Package Mechanical Data-PDFN5*6-8L-JQ Single



Symbol	Common			
	mm		Inch	
	Min	Max	Min	Max
A	1.03	1.17	0.0406	0.0461
b	0.34	0.48	0.0134	0.0189
c	0.824	0.0970	0.0324	0.082
D	4.80	5.40	0.1890	0.2126
D1	4.11	4.31	0.1618	0.1697
D2	4.80	5.00	0.1890	0.1969
E	5.95	6.15	0.2343	0.2421
E1	5.65	5.85	0.2224	0.2303
E2	1.60	/	0.0630	/
e	1.27 BSC		0.05 BSC	
L	0.05	0.25	0.0020	0.0098
L1	0.38	0.50	0.0150	0.0197
L2	0.38	0.50	0.0150	0.0197
H	3.30	3.50	0.1299	0.1378
I	/	0.18	/	0.0070

Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
TAPING	PDFN5*6-8L		5000