

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.9.12	阿树

■SPECIFICATIONS

- Voltage rating:250V AC/DC
- Current rating:3A AC/DC
- Withstanding Voltage:1000V AC/minute
- Temperature range:−40°C~+125°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤10mΩ
- After environmental testing:≤20mΩ

PART NO.:

X2564 H-XX-N0
① ② ③ ④

- ①Series No
②Category:H-HSG
③Row No.Pin No:XX-02~16P
④Material:N0-PA66 UL94V-0

POLES	A	B	C	POLES	A	B	C
2	2.50	7.50	5.90	10	22.50	27.50	25.90
3	5.00	10.00	8.40	11	25.00	30.00	28.40
4	7.50	12.50	10.90	12	27.50	32.50	30.90
5	10.00	15.00	13.40	13	30.00	35.00	33.40
6	12.50	17.50	15.90	14	32.50	37.50	35.90
7	15.00	20.00	18.40	15	35.00	40.00	38.40
8	17.50	22.50	20.90	16	37.50	42.50	40.90
9	20.00	25.00	23.40				

X2564H-XX-N0	Nyoln 66 UL 94V-0	X2564T	X2564W
PART NO	Material	Suitable XKB Terminal	Suitable XKB Terminal

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树	VIEW:		MODEL TYPE: 2.50mm Crimp Style Connectors
CHECKED		UNIT:	mm/in	PART NO.: X2564H-XX-N0
APPROVED		SIZE:	A4	DWG NO.:

XKB INDUSTRIAL PRECISION CO.,LIMITED			SCALE N/A	PAGE 1/1	REVISION A1
--------------------------------------	--	--	--------------	-------------	----------------

