

COAXIAL ADAPTER, PC 1.85, 50 Ohm, plug / jack (male / female)

33_PC185-50-0-1/199_NE

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings

**Product configuration**

Interface type	Gender	Standard
PC 1.85	plug (male)	IEC 60169-32
PC 1.85	jack (female)	IEC 60169-32

Interface and material data

PC 1.85		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	
Coupling nut	Stainless Steel	Passivated (Plating)
PC 1.85		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Body		Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	

Electrical data

Impedance	50 Ω
Interface frequency	67 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 30 GHz	28 dB	1.083
30 GHz ... 50 GHz	25 dB	1.119
50 GHz ... 67 GHz	23 dB	1.152

COAXIAL ADAPTER, PC 1.85, 50 Ohm, plug / jack (male / female)

33_PC185-50-0-1/199_NE

Mechanical data	
Weight	0.0056 kg
Mating cycles	500

Environmental data	
Operation temperature	-55 °C ... 155°C

Ordering Information Table	
Item number	Item description
84019546	33_PC185-50-0-1/199_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2185 / Date of publication: 26.11.2023 / uncontrolled copy