



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**

Connector & Housing Type: **Receptacle**

Number of Positions: **1**

Terminal Orientation: **Straight**

UL Flammability Rating: **UL 94V-0**

Features

Product Type Features

Sealable	No
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	Without

Mechanical Attachment

--



Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Length	24.7 mm[.97 in]
----------------	-----------------

Usage Conditions

Operating Temperature Range	-25 – 170 °C[-13 – 338 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	7500
--------------------	------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2-1644125-3
SLEEVE ESPRING 250 NYLON DARK GRY



TE Part # 2-1644125-4
SLEEVE EPRING 250 PA DARK GRY



TE Part # 9-1644125-4
ESPRING SLEEVE 250 HIGH TEMP NYLON BLK

Also in the Series | FASTON 250



Compression Connectors(4)



Crimp Terminal Housings(132)



Insertion & Extraction Tools(6)



Magnet Wire Terminals(1)



PCB Terminals(134)



Quick Disconnects(426)



Splices(4)


Customers Also Bought



TE Part #175149-1
UNIVERSAL POWER CONN TAB



TE Part #176281-1
UNIV POWER CAP HSG 1P F/H



TE Part #175151-1
AMP UNIVERSAL POWER REC CONT.



TE Part #63933-2
250 PL MKIII REC. 22-18AWG TPBR



Documents

Product Drawings
E SPRING .250 (6.3 MM) RECEPTACLE

English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_2-1644125-8_E_c-2-1644125-8-e.2d_dxf.zip
English
Customer View Model
ENG_CVM_CVM_2-1644125-8_E_c-2-1644125-8-e.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_2-1644125-8_E_c-2-1644125-8-e.3d_stp.zip
English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages
E-Spring Flyer

English

Product Specifications
6,35 E-SPRING CONTACT RECEPTACLES SLEEVES

English

Application Specification
English

2-1644125-8

Receptacle, Receptacle, 1 Position, Straight, UL 94V-0, Natural, Polyamide, Mating Alignment, FASTON 250, Crimp Terminal Housings

