SCHRACK | SCHRACK Relay Package XT

TE Internal #: 2-1415073-1

General Purpose Power Relay, Monostable, .76 VA Coil Power Rating AC, 350 ohm Coil Resistance, SCHRACK Relay Package XT,

Power Relays

View on TE.com >



Relays & Contactors > Relays > Power Relays



Relay Type: General Purpose Power Relay

Coil Magnetic System: Monostable
Coil Power Rating Class: [.5 – 1 VA]
Coil Power Rating AC: .76 VA

Coil Resistance: 350Ω

Features

Product Type Features

Relay Type	General Purpose Power Relay
Configuration Features	
Contact Arrangement	2 Form C DPDT-CO
Contact Number of Poles	2
Electrical Characteristics	
Insulation Initial Dielectric Between Open Contacts	1000 Vrms
Contact Limiting Making Current	15 A
Contact Limiting Short-Time Current	8 A

Contact Limiting Making Current	15 A
Contact Limiting Short-Time Current	8 A
Contact Limiting Continuous Current	8 A
Insulation Initial Dielectric Between Adjacent Contacts	2500 Vrms
Insulation Initial Dielectric Between Contacts & Coil	5000 Vrms
Contact Limiting Breaking Current	8 A
Coil Power Rating AC	.76 VA
Coil Resistance	350 Ω
Coil Voltage Rating	24 VAC
Contact Current Rating	8 A
Contact Switching Voltage (Max)	400 VAC



Contact Valtage Pating	240 \/ \ C
Contact Voltage Rating	240 VAC
Body Features	
Product Weight	54 g[1.905 oz]
Contact Features	
Contact Plating Material	Gold
Contact Material	AgNi90/10
Termination Features	
Relay Connection Type	Plug-In
Terminal Configuration	Screw Terminals
Mechanical Attachment	
Product Mount Type	DIN Rail
Dimensions	
Insulation Clearance Between Contact & Coil	10 mm[.394 in]
Insulation Creepage Between Contact & Coil	10 mm[.394 in]
Product Width	15.8 mm[.622 in]
Product Length	69 mm[2.71 in]
Product Height	77 mm[3.03 in]
Usage Conditions	
Environmental Category of Protection	RTI
Environmental Ambient Temperature (Max)	70 °C[158 °F]
Operating Temperature Range	-20 – 70 °C
Operation/Application	
Current Type	AC
Indicator Type	LED
Coil Magnetic System	Monostable
Packaging Features	
Packaging Method	Carton
Other	
Environmental Ambient Temperature Class	50 – 70 °C
Width Class (Mechanical)	12 – 16 mm
	.5 – 1 VA



Contact Current Class 16 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | SCHRACK Relay Package XT





Customers Also Bought


















Documents

CAD Files

Customer View Model

ENG_CVM_CVM_2-1415073-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2-1415073-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2-1415073-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

Relay Package Package RT

English

General Purpose Power Relay, Monostable, .76 VA Coil Power Rating AC, 350 ohm Coil Resistance, SCHRACK Relay Package XT, Power Relays



Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

UKCA_CERT_708_00005_C1

English