

Catalog No. TYHT27M

Description: CABLE TIE 120LB 13IN OLV NYL HI TEM

UPC No 786210952727

Home > Wire & Cable Management > Ty-Rap > Cable ties

Extra High Temperature Cable Tie, Olive Polyamide (Nylon 4.6) for Temperatures up to 150 Degrees Celsius (302 F) for High Temperature Environments, Length of 343mm (13.5 Inches), Width of 6.9mm (0.27 Inch), Thickness of 1.5mm (0.06 Inch), Tensile Strength Rating of 534 Newtons (120 Pounds)

Representative Image

Descriptors

| | |
|------------------|--|
| Category | Cable ties |
| Type | Extra High Temperature |
| Special Features | Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. |

Specifications

| | |
|------------------|--------------------------|
| Material | Nylon/Polyamide 4.6 |
| Color | Olive |
| Lock Mechanism | Stainless Steel Barb |
| Tensile Strength | 120 pounds , 534 newtons |

Classifications

| | |
|------------|-----------|
| Brand Name | Ty-Rap |
| Standard | UL E49405 |

Dimensions

| | |
|-----------------|---------------------------------|
| Width | 0.27 in , 6.9 mm |
| Length | 13.5 in , 343 mm |
| Thickness | 0.06 in , 1.5 mm |
| Bundle Diameter | 0.187 to 3.5 in , 4.75 to 89 mm |

Compliance and Certifications

| | |
|------|-----------------|
| RoHS | RoHS3 Compliant |
|------|-----------------|

ETIM Classification

| | |
|------------|--------------------|
| ETIM | EC000046 Cable tie |
| Band width | 6.9 mm |

| | |
|--|--------------------|
| ETIM | EC000046 Cable tie |
| Length belt/tape/tie | 343 mm |
| Length belt/tape/tie | 13.4 inch |
| Tie thickness | 1.5 mm |
| Tie thickness | 0.06 inch |
| Max. bundle diameter | 89 mm |
| Min. holding force | 534 N |
| Operation temperature | -40-+150 °C |
| Operation temperature | -40-+302 °F |
| Model | Internal toothing |
| Band closure | Steel nose |
| Material | Plastic |
| Material quality | Polyamide (PA) |
| Surface protection | Untreated |
| UV-stable acc. ASTM D6779 | N |
| Halogen free | Y |
| Colour | Other |
| Transparent | N |
| Reflective (fluorescent) | N |
| Text strip | None |
| Solvable fastener | N |
| VG approval | N |
| MIL approval | N |
| UL approval | Y |
| Inflammability class of insulation material acc. with UL94 | V2 |