

AMP | AMP CPC

TE Internal #: 211401-8

Housing, 600 VDC, Wire-to-Wire, 7 Position, Wire & Cable, Receptacle, Pin, Power & Signal, Black, All Plastic, AMP CPC,

Circular Power Connectors

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors











Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 7

Sealable: No

Features

Product Type Features

Connector Product Type	Housing
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Circular Connector Shell Type	All Plastic

Configuration Features

Reverse Numbering	Without
Number of Positions	7
Number of Power Positions	0
Number of Signal Positions	7

Electrical Characteristics

Operating Voltage	600 VAC

Contact Features



Reverse Gender	No
Contact Type	Pin
Contact Protection	With
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Panel Mount Feature Type	Flange with Mounting Holes
Mating Retention Type	Threaded Coupling
Thread Size	3/4 - 20 UNEF-2A
Polarization Code	A
Connector Mounting Type	Panel Mount
Mating Retention	With
Panel Mount Feature	With
Housing Features	
Body Orientation	Straight
Housing Color	Black
Housing Material	Nylon, Thermoplastic
Housing Material Circular Connector Shell Size	Nylon, Thermoplastic 13
Circular Connector Shell Size	
Circular Connector Shell Size Usage Conditions	13
Circular Connector Shell Size Usage Conditions Operating Temperature Range	13 -55 – 105 °C[-67 – 221 °F]
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance	13 -55 – 105 °C[-67 – 221 °F]
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application	13 -55 – 105 °C[-67 – 221 °F] None
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application	13 -55 – 105 °C[-67 – 221 °F] None Power & Signal
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded	13 -55 – 105 °C[-67 – 221 °F] None Power & Signal
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards	13 -55 – 105 °C[-67 – 221 °F] None Power & Signal No
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards Compatible With Agency/Standards Products	13 -55 – 105 °C[-67 – 221 °F] None Power & Signal No
Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards Compatible With Agency/Standards Products UL Flammability Rating	13 -55 – 105 °C[-67 – 221 °F] None Power & Signal No

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | AMP CPC





Circular Power Connectors(425)



Connector Backshells(1)



Connector Caps & Covers(16)



Connector Contacts(6)



Connector Hardware(12)




Connector Seals & Cavity Plugs(35)



Connector Strain Relief(60)



Insertion & Extraction Tools(1)



Customers Also Bought


















Documents



Product Drawings

RECEPT,SZ 13-7,CPC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_211401-8_AE.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_211401-8_AE.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_211401-8_AE.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Instruction Sheet (U.S.)

English

Agency Approvals

CSA Certificate

English