



Product: [9531](#)

Lead Wire on Racks, 5 C #22 Str TC, PVC Ins, Five Color Kit

[Request Sample](#)

Product Description

Low Temp Plastic Lead Wire on Racks, 5 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, Five Color Kit 80C

Technical Specifications

Product Overview

Suitable Applications:	inter-connection circuits, internal wiring of computer and electronic equipments, internal wiring of appliances
------------------------	---

Physical Characteristics (Overall)

Conductor		
AWG	Stranding	Material
22	7x30	TC - Tinned Copper
Conductor Count:		1

Insulation	
Material	
PVC - Polyvinyl Chloride	

Temperature Range

UL Temp Rating:	80°C
-----------------	------

Mechanical Characteristics

Bulk Cable Weight:	15 lbs/1000ft
--------------------	---------------

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
CA Prop 65:	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
--------------------	-----

Related Part Numbers

Variants			
Item #	Put-Up Type	Length	UPC
9531	Reel	1 ft	612825255017

Product Notes

Notes:	5 Spools of 8524 in the following colors 2, 5, 6, 9, 10 - Spool Lengths 100 Ft.
--------	---

History

Update and Revision:	Revision Number: 0.335 Revision Date: 05-05-2023
----------------------	--

© 2024 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.