

# **Specification Sheet**

Part Number: 596-00828



Metal Solar Placard, WARNING ELECTRICAL SHOCK...Hand Writable, 3.75"x2.0", AA, Orange/Silver, 5/pkg

Article Number	596-00828
Туре	WESHLBLM5
Color	Orange (OG)
Features & Benefits	• Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure. • Aggressive adhesive ensures strong bond, even on powder coated surfaces. • Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability. • Optional Paint Shields provide additional protection for pre-printed and variable data placards.
Quantity Per	pack

Product	Description

Variable data placards are used to mark areas specific to the individual installation, like voltage data. Made of the same durable material as pre-printed metal solar placards, HellermannTyton offers two styles of variable placards: hand-writable and engravable. Both hand-writable placards feature a silver variable data area that can be marked using an industrial paint pen. Engravable placards have a black area that can be engraved using standard engraving equipment.

## **Short Description**

Metal Solar Placard, WARNING ELECTRICAL SHOCK...Hand Writable, 3.75"x2.0", AA, Orange/Silver, 5/pkg

**Global Part Name** 

WESHLBLM5-AA-OG

**Technical Description** 

3.75" X 2" Black text on an Orange/Silver Aluminum background that reads as: "WARNING ELECTRICAL SHOCK HAZARD. DO NOT TOUCH TERMINALS. TERMINALS ON BOTH LINE AND LOAD SIDE MAY BE ENERGIZED IN THE OPEN POSITION." - 5 per pack.

**Local Order Number 2** 

Cross Reference = Paint Shield: 596-00793

l enath l	(Imperial)
LCHQUI L	(IIII)

2.0

#### Length L (Metric)

50.8

#### Width W (Imperial)

3.75

## Width W (Metric)

95.25

#### Height H (Imperial)

2.0

# Height H (Metric)

50.80

# Material

Anodized Aluminum (AA)

Material Shortcut	AA
Adhesive	Ultra High Bond Permanent Acrylic Adhesive
Halogen free	No
Adhesive Operating Temperature	from +50°F (from +10°C)
Operating Temperature (Metric)	-40°F to +203°F (-40°C to +95°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2014
Warranty (US)	Yes
Package Quantity(Imperial)	5
Package Quantity (Metric)	5
Customs Number	7616995195
Labels per Column	1
Labels per Row	1
Weight (Metric)	.104
Weight (Imperial)	0.23

