




MAPX	MODIFICATION	DATE

- Note:
- 1.Material:
 - 1.1,Housing: High temperature thermoplastic with/black G/F,UL94v-0
 - 1.2,Contact: copper alloy,t=0.25mm
 - 1.3,Shell: copper/Ferroalloy alloy,t=0.30mm
 - 2.Specification:
 - 2.1,Current rating:1.5A Max.
 - 2.2,Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - 2.3,Contact resistance: 30 mΩ Max.
 - 2.4,Insulation resistance: 100 MΩ Min.
 - 2.5,Total mating force: 3.57 Kgf Max.
 - 2.6,Total unmating force: 1.0 Kgf Min.
 - 3.Finish:
 - 3.1,Contact: Plated Golg in Mating Area: Tin On Solder Talls
 - Shell: Nickel Plating
 - 4.Environmental:
 - 4.1,Temperature range: -55°C~85°C

PART ON:
907-222AXXX1Y1XX

- 电镀规格: 02, 镀金1u" 04, 镀金3u" 07, 镀金15u" 08, 镀金30u"
- 端子材质: 1, 青铜 2, 磷铜
- 端子规格: D, 90度 Y, 180度 S, SMT贴板
- 塑胶形态: 1, 双层短体 2, 双层半包
- 塑胶颜色: 01, 白色 02, 黑色 03, 本色
- 塑胶材质: 1, PBT 2, LCP 3, PA9T 4, PPA 5, PA6T
- 对插方向: A, 正向 B, 反向
- 外壳材质: 1, 铁壳 2, 铜壳
- 插口类型: 1, 有边平弹 2, 无边平弹
- 外壳脚型: 1, 弯脚 2, 直脚 3, 无脚 4, 鱼叉脚
- 类别: 双层系列

产品图 PRODUCT CHART DWG				深圳市精拓金电子有限公司					
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	YANG	制图料号 PRODUCT PART NO.	907-322A1011Y10200
X.	±0.30	X.	±5.°	比例 SCALE	1:1	审核 CHKD	郭志富	产品名称 PRODUCT NO.	AF180度10.5双层无脚无边平弹 铜壳PBT防火白胶
.X	±0.25	.X	±2.°	日期 DATE	2019.11.23	核准 APPD	黄国荣	角法 VIEW	
.XX	±0.15	.XX	±1.°					版本 VER	AO
.XXX	±0.10	.XXX	±0.5°						