

PRODUCTS

[Rocker switches](#)[Pushbutton switches](#)[Toggle switches](#)[Slide switches](#)**[Rotary switches](#)**[Foot switches](#)[Tact and key switches](#)[Snap-action switches](#)[Micro-signal switches](#)[ECO switches](#)[Sensors](#)[Systems and modules](#)[Accessories](#)[General information](#)[Catalog request /
download](#)PRODUCTS ▶ [ROTARY SWITCHES](#)


Rotary switches

SERIES 1703 - POWERFUL ROTARY SWITCHES - TO 20 (4) A 400 V AC

[Show next product ▶](#)

1703.3201

[Drawing](#)Similar to original
product[→ Print data sheet](#)

Product number	1703.3201
Actuator color / printing	
Miscellaneous	1 switching step (60°)
Switching function	ON / OFF switch (DPST)
Number of poles	2-pole
connections	Quick-connect terminal, 6.3
Mechanical life endurance	3E4
Rating IEC	20 (4) A 400 V AC 1E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	400 PTI
Protection type	Connection IP 40
Ambient temperature	-20 °C ... +100 °C ... +55 °C
Flammability	UL 94 (housing: V-0, spindle: V-2)
Glow wire test temperature	850 °C
Actuators and additional actuators	PA, black
Housing description	PA glass fiber-reinforced, brown
Connection surface	external connection silver plated respectively bare
Contact material	Ag
Contact distance	≥ 3 mm
Plug force of the terminals	≤ 80 N
Approval marks	ENEC 10
Suitable for appliances of protection class	I