



## Fittings for metallic conduits

### • SC-FF Fixed Internal Thread

Fixed internal thread, nickel plated brass.


#### Features and Benefits

- Two-part fitting of shell and body with internal thread
- Provides tight, reliable hold of conduit
- Can be used to couple two conduits together when used with swivel fitting



HelaGuard SC-FF Fixed Internal Thread.

|                              |                           |
|------------------------------|---------------------------|
| <b>MATERIAL</b>              | Nickel Plated Brass (NPB) |
| <b>Operating Temperature</b> | -100 °C to +300 °C        |



HelaGuard fitting, straight with fixed internal thread

| TYPE        | Nominal Ø | Thread Size | Min. Bore Size (B) | Length (L) | A/F Body (A/F1) | Thread Length (TL) | Pack Cont. | Colour     | Article-No. |
|-------------|-----------|-------------|--------------------|------------|-----------------|--------------------|------------|------------|-------------|
| SC16-FF-M20 | 16        | M20         | 11.5               | 24.5       | 22              | 10.0               | 10 pcs.    | Metal (ML) | 166-30600   |
| SC20-FF-M20 | 20        | M20         | 15.3               | 26.0       | 24              | 10.0               | 10 pcs.    | Metal (ML) | 166-30601   |
| SC25-FF-M25 | 25        | M25         | 19.1               | 30.0       | 29              | 12.0               | 10 pcs.    | Metal (ML) | 166-30602   |
| SC32-FF-M32 | 32        | M32         | 26.2               | 33.3       | 36              | 13.0               | 2 pcs.     | Metal (ML) | 166-30603   |

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.