

AMP | AMP CPC

TE Internal #: 206852-8

Connector Assembly, 250 VDC, Wire-to-Panel, 9 Position, Printed

Circuit Board, Receptacle, Pin, Signal, Black, AMP CPC, Circular

Power Connectors

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors > Connectors, CPC Series 2, with Posted Contacts











Connector Product Type: Connector Assembly

Operating Voltage: 250 VDC

Connector System: Wire-to-Panel

Number of Positions: 9

Sealable: No

All Connectors, CPC Series 2, with Posted Contacts (8)

Features

Product Type Features

Operating Voltage

Connector Product Type Connector System Wire-to-Panel Sealable No Connector & Contact Terminates To Printed Circuit Board Connector & Housing Type Receptacle Circular Connector Shell Type All Plastic Configuration Features Number of Positions 9 Number of Power Positions 0		
Sealable No Connector & Contact Terminates To Printed Circuit Board Connector & Housing Type Receptacle Circular Connector Shell Type All Plastic Configuration Features Number of Positions 9 Number of Power Positions 0	Connector Product Type	Connector Assembly
Connector & Contact Terminates To Printed Circuit Board Connector & Housing Type Receptacle Circular Connector Shell Type All Plastic Configuration Features Number of Positions 9 Number of Power Positions 0	Connector System	Wire-to-Panel
Connector & Housing Type Circular Connector Shell Type All Plastic Configuration Features Number of Positions 9 Number of Power Positions 0	Sealable	No
Circular Connector Shell Type Configuration Features Number of Positions 9 Number of Power Positions 0	Connector & Contact Terminates To	Printed Circuit Board
Configuration Features Number of Positions 9 Number of Power Positions 0	Connector & Housing Type	Receptacle
Number of Positions9Number of Power Positions0	Circular Connector Shell Type	All Plastic
Number of Power Positions 0	Configuration Features	
	Number of Positions	9
Number of Signal Positions 9	Number of Power Positions	0
,	Number of Signal Positions	9
Electrical Characteristics	Electrical Characteristics	

250 VAC



Contact Features

Reverse Gender	No
Contact Type	Pin
Contact Current Rating (Max)	7.5 A
Contact Protection	With

Termination Features

Tamainatian Mathaalta DCD	Thurst als III als Callalan
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Alignment	With
Panel Mount Feature Type	Flange with Threaded Inserts
Mating Retention Type	Threaded Coupling
Connector Mounting Type	Panel Mount
Mating Retention	With
Panel Mount Feature	With

Housing Features

Housing Color	Black
Housing Material	Thermoplastic
Circular Connector Shell Size	11

Dimensions

Compatible Insulation Diameter Range	1.73 mm[.068 in]
Companier insulation Diameter Kange	1.73 11111[.000 111]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Fluid Resistance	None

Operation/Application

Circuit Application	Signal
Shielded	No

Industry Standards

UL Flammability Rating	UL 94V-0	

Packaging Features

Packaging Quantity	40
Packaging Method	Tray



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts















Also in the Series | AMP CPC



Circular Power Connectors(458)



Connector Backshells(1)



Connector Caps & Covers(19)



Connector Contacts(6)



Connector Hardware(12)




Connector Seals & Cavity Plugs(36)



Connector Strain Relief(60)



Insertion & Extraction Tools(1)



Customers Also Bought























Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_206852-8_AL.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_206852-8_AL.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_206852-8_AL.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

Product Specifications

Connector, Circular Plastic

English

Product Specification

English