

# DATASHEET


## C0402C0G250-680JNE

GENERAL PURPOSE CERAMIC CAPACITORS (C SERIES)

0402, C0G, 25V, 68pF,  $\pm 5\%$ , 100% matte Tin(Sn) over Nickel



VENKEL LTD.



### SIZE SPECIFICATIONS units: inches

|            |       |
|------------|-------|
| Length:    | 0.040 |
| Width:     | 0.020 |
| T(max):    | 0.025 |
| Min E/B:   | 0.004 |
| Size(EIA): | 0402  |

### COMPONENT SPECIFICATIONS

|                    |                                |
|--------------------|--------------------------------|
| Category:          | Ceramic Capacitors             |
| Series:            | General Purpose (C Series)     |
| Size:              | 0402                           |
| Dielectric:        | C0G                            |
| Voltage:           | 25V                            |
| Capacitance:       | 68pF                           |
| Tolerance:         | $\pm 5\%$                      |
| Termination:       | 100% matte Tin(Sn) over Nickel |
| Packaging:         | E                              |
| Quantity per Reel: | 10,000                         |

### DIELECTRIC SPECIFICATIONS

|                                 |                                       |
|---------------------------------|---------------------------------------|
| Temperature Coefficient:        | 0 $\pm 30$ PPM/ $^{\circ}$ C          |
| Temperature Voltage Coefficient | 0 $\pm 30$ PPM/ $^{\circ}$ C          |
| Ageing:                         | None                                  |
| Withstanding Voltage:           | 2.5 times VDCW                        |
| Operating Temp:                 | -55 $^{\circ}$ C to +125 $^{\circ}$ C |
| Dissipation Factor:             | 0.1% max                              |

### ENVIRONMENTAL INFORMATION

|                            |                       |
|----------------------------|-----------------------|
| RoHS Status                | 6 of 6 Compliant      |
| REACH Status               | Compliant             |
| Halogen Status             | Halogen Free          |
| Conflict Mineral Status    | Conflict Mineral Free |
| Moisture Sensitivity Level | MSL1                  |

### REFLOW PROFILE

|                          |                  |
|--------------------------|------------------|
| Max Reflow Temperature   | 260 $^{\circ}$ C |
| Number of Reflow Cycles  | 2                |
| Time at Max Reflow Temp. | 10 sec           |

### REEL DIMENSIONS units: mm

| Tape | B min | C            | A(7")         | A(13")        | D Min | N Min | G            | T max |
|------|-------|--------------|---------------|---------------|-------|-------|--------------|-------|
| 8mm  | 0.30  | 13 $\pm$ .05 | 178 $\pm$ 2.0 | 330 $\pm$ 2.0 | 20.20 | 50.00 | 10 $\pm$ 1.5 | 14.90 |

### TAPING SPECIFICATIONS units: mm

| A                    | B              | W             | F              | E              | Po            |
|----------------------|----------------|---------------|----------------|----------------|---------------|
| 0.65 $\pm$ 0.1       | 1.10 $\pm$ 0.2 | 8.0 $\pm$ 0.2 | 3.5 $\pm$ 0.1  | 1.75 $\pm$ 0.1 | 4.0 $\pm$ 0.1 |
| Pz                   | D              | T             | P              | To             | T(E)          |
| 2.0 $\pm$ 0.05 - 0.0 | 1.5 $\pm$ 0.1  | 1.15 MAX      | 2.0 $\pm$ 0.05 |                |               |