

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.9.03	阿树

PART NO.:

X1255 W R S-XX A-LP XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ①Series No
②Category: W-Wafer
③Welding Board Angle: R-Stright 90°
④Welding Way: S-SMT
⑤Row No.Pin No: XX-02~14Pin
⑥Plug the Pin & Special NO: A-Double Dole
⑦Material : 9T-PA9T 94V-0; 1T-PA10T
⑧Planting Category: V01: All Gold Flash
SW-Matte tin plating

■SPECIFICATIONS

- Voltage rating: 200V AC/DC
- Current rating: 1A AC/DC
- Withstanding Voltage: 500V AC/minute
- Temperature range: -40°C~+125°C
- Insulation resistance: $\geq 100M\Omega$
- Contact resistance: $\leq 40m\Omega$
- After environmental testing: $\leq 80m\Omega$

Poles	Dimensuons (mm)		
	A	B	C
02	6.00	1.25	3.30
03	7.25	2.50	4.55
04	8.50	3.75	5.80
05	9.75	5.00	7.05
06	11.00	6.25	8.30
08	13.50	8.75	10.80
09	14.75	10.00	12.05
10	16.00	11.25	13.30
11	17.25	12.50	14.55
12	18.50	13.75	15.80
13	19.75	15.00	17.05
14	21.00	16.25	18.30

X1255WRS-XXA-LPSWBK	LCP UL 94V-0	Brass	Tin-Plated	X1255H
X1255WRS-XXA-LPV01			Gold-Flash	
X1255WRS-XXA-LPSW			Tin-Plated	
PART NO	Material	Material (Pin&Solder Tab)	Finish (Pin)	Suitable XKB Terminal

AuGLAR	$\pm 5^\circ$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树	VIEW:	MODEL TYPE: 1.25mm Crimp Style Connectors
CHECKED		UNIT: mm/in	PART NO.: X1255WRS-XXA-LPSWBK
APPROVED		SIZE: A4	DWG NO.:

SCALE	PAGE	REVISION
N/A	1/1	A1