



Part Number : 1552100230

Series Number : 155210

Product Category : Industrial Cable

Product Description : Flamar Control Cable, PVC Jacket, Unshielded, 4 Circuits, 1.50mm² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 7.90mm (.311") Diameter, 500.0m (1640.42') Length, Black

Status : Obsolete

Engineering Number : 1X500M

Documents & Resources

Product Environment Compliance

Compliance

| | |
|--------------------|--------------|
| China RoHS | Not Reviewed |
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------|------------------|
| Status | Obsolete |
| Category | Industrial Cable |
| Series | 155210 |

| | |
|-----------------|--|
| Description | Flamar Control Cable, PVC Jacket, Unshielded, 4 Circuits, 1.50mm ² with Green-Yellow Ground / 16 AWG with Green-Yellow Ground, 7.90mm (.311") Diameter, 500.0m (1640.42') Length, Black |
| Geographic Area | Global |
| Product Family | Flamar Standard and Custom Cables for Industrial Automation |
| Product Name | Flamar,Signal and Control |
| UPC | 889056453288 |

Electrical

| | |
|-------------------------------|---------------|
| Current - Maximum per Contact | Contact Molex |
| Voltage - Maximum | 300V |

Physical

| | |
|-------------------------------|-------------------|
| Bending Radius - Minimum | > 15xOD |
| Cable Length | 500.0m |
| Circuits (Loaded) | 4 |
| Color - Cable Jacket | Black |
| Insulation | TPE |
| Material - Outer Jacket | PVC |
| Net Weight | 0.010/g |
| Outer Jacket Diameter | 7.90mm |
| Packaging Type | Reel |
| Temperature Range - Operating | +5° to +80°C |
| Wire/Cable Type | UL AWM 2464 / CSA |
| Wire Size (AWG) | 16 |
| Wire Size mm ² | 1.50 |