

HDP26-24-14PN-L017

✓ ACTIVE

DEUTSCH | [DEUTSCH HD](#), [DEUTSCH HDP](#)

TE Internal #: HDP26-24-14PN-L017

Housing for Male Terminals, Wire-to-Panel, 14 Position, Sealable, Black, Wire & Cable, Power, Panel Mount, -55 – 125 °C [-67 – 257 °F], Hybrid

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH HDP20 Housings



Connector System: **Wire-to-Panel**
Number of Positions: **14**
Connector & Housing Type: **Housing for Male Terminals**
Sealable: **Yes**
Mating Pin Diameter: **1.6 mm, 2.4 mm, 5.7 mm [.063 in, .094 in, .225 in]**

[All DEUTSCH HDP20 Housings \(357\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Circular
Connector System	Wire-to-Panel
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Contact Retainer

Configuration Features

Blank Cavity Position	0
Connector Modification	Ring Adapter
Connector Seal Code	N Seal
Number of Positions	14



Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	250 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black

Contact Features

Contact Size	Size 12, Size 16, Size 4
Contact Type	Pin
Mating Pin Diameter	1.6 mm, 2.4 mm, 5.7 mm[.063 in][.094 in][.225 in]
Contact Current Rating (Max)	13 A, 25 A, 100 A

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarizing Slot
Mating Alignment	With
Connector Mounting Type	Panel Mount

Housing Features

Housing Material	PA 66 GF
------------------	----------

Dimensions

Connector Height	42.5 mm[1.67 in]
Product Width	49.5 mm[1.95 in]
Product Length	49.5 mm[1.95 in]
Compatible Insulation Diameter Range	1.4 – 3.8 mm, 3.6 – 5.2 mm[.055 – .15 in][.14 – .204 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

--	--



Degree of Protection	IP67
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	40
Packaging Method	Tray

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>




EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.4% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # CAT-D48-SP729 DEUTSCH Sealing Plugs	 TE Part # CAT-D48-ST273 DEUTSCH Solid Contacts	 TE Part # CAT-H396-B128 DEUTSCH HDP20 Backshells	 TE Part # CAT-J67-DSCC16 DEUTSCH Size 16 Crimp Contacts
 TE Part # HD30-24BT-BK BOOT, 24SZ, ST, BLK	 TE Part # 1060-12-0144 PIN, SF, SIZE 12, 12-14, AU/SN	 TE Part # 1060-12-0166 PIN, SF, SIZE 12, 12-14, NI/SN	 TE Part # 2300908-1 0460-003-16329, PIN, SOLID, 20-24AWG, AU
 TE Part # CAT-H396-CH8172 DEUTSCH HDP20 Housings	 TE Part # 114009-ZZ EXT TOOL, SIZE 4, 6 AWG, N, WHT	 TE Part # 0411-291-1405 EXT TOOL, SIZE 16, 14-16 AWG, N, GRN	 TE Part # 114010-ZZ EXT TOOL, SIZE 12, 12 AWG, N, YEL
 TE Part # 0411-204-1605 EXT TOOL, SIZE 16, 16-18 AWG, N, DRK BLU	 TE Part # 1060-12-0222 PIN, SF, SIZE 12, 10, NI/NI	 TE Part # HD30-24BT BOOT, 24SZ, ST, GRY	 TE Part # HD30-24BT-90-BK BOOT, 24SZ, RA, BLK
 TE Part # CAT-D48-SFT273 DEUTSCH Stamped and Formed Contacts	 TE Part # HDP24-24-14SN-L015 REC, 14P, BLK, N, THD, 4/12/16, S		

Also in the Series | **DEUTSCH HD**



Automotive Connector Caps & Covers
(32)

Automotive Housings(768)

Connector Backshells(29)

Connector Seals & Cavity Plugs(10)

Connector Strain Relief(5)

Insertion & Extraction Tools(11)

Other Automotive Connector
Accessories(11)

PCB Headers & Receptacles(1)

Also in the Series

DEUTSCH HDP

Automotive Connector Caps & Covers
(4)

Automotive Housings(357)

Connector Backshells(8)


Connector Seals & Cavity Plugs(1)

Insertion & Extraction Tools(11)

Other Automotive Connector
Accessories(5)

Customers Also Bought



 TE Part #205204-8 HDP-20,PLUG,SIZE 1, 9 POSN	 TE Part #1-967059-1 J-P-T GEH KOMPL 4P	 TE Part #66506-9 PIN CONTACT, 20 DF	 TE Part #42281-1 FF 250 REC 18-14AWG BR
 TE Part #60249-1 FF 250 REC 16-12AWG BR	 TE Part #1-480705-0 06P UMNL CAP HSG NATL	 TE Part #114019-ZZ SEALING PLUG, SIZE 4, WHT	 TE Part #DT06-3S-CE01 PLG, 3P, GRY, E, CAP
 TE Part #929937-3 JPT REC 2.8 Contact SWS Sn	 TE Part #3-1393310-8 VCFM-1002=SOCKET,VCFM,5,PC,PLA-		

Documents

Product Drawings

PLG, 14P, BLK, N, RNG, 4/12/16, P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_HDP26-24-14PN-L017_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_HDP26-24-14PN-L017_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_HDP26-24-14PN-L017_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



[ICT Terminals and Connectors Catalogue](#)

English

[CONNECTOR SELECTOR](#)

English

[Product Specifications](#)

[Application Specification](#)

English

[Agency Approvals](#)

[UL Report](#)

English