

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter



1162417

<https://www.phoenixcontact.com/us/products/1162417>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VIP VARIOFACE front adapter, with connected system cables for ControlLogix® 1756 I/O. Up to 1 x 16 channels can be connected.

Your advantages

- Individual I/O modules lock to the controller for connection security
- Disconnect lever aids in removal from I/O card
- Marking label can be attached
- Pluggable push in terminals on adapter for returns connections
- Shield connection: UL Type AWM, Style 1007 18 AWG (0.82 mm²) cable, black, 0.5 m length

Commercial data

Item number	1162417
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C423
Product key	CK232R
GTIN	4063151172725
Weight per piece (excluding packing)	504 g
Customs tariff number	85444290
Country of origin	DE

1162417

<https://www.phoenixcontact.com/us/products/1162417>

Technical data

Product properties

Product type	Front adapter
Product family	VARIOFACE Professional

Data management status

Article revision	00
------------------	----

Insulation characteristics

Overvoltage category	II
Pollution degree	2

Electrical properties

Max. permissible operating voltage	60 V DC
Max. permissible current	1 A (per path)
	6 A (total, RTN terminals)

Supported controller ALLEN-BRADLEY ControlLogix

Suitable I/O card	1756-OF8
	1756-OF8H

Connection data

Controller level

Connection method	Plug-in connection
Note	Can be plugged onto 20-pos. I/O modules

Field level

Connection in acc. with standard	IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	2
Number of positions	14
Pitch	2.54 mm

Return

Connection method	Push-in / plug connection
Stripping length	9 mm
Conductor cross section rigid	0.14 mm ² ... 1.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	26 ... 16

Dimensions

Item dimensions

Width	355.98 mm
Height	47.28 mm

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter



1162417

<https://www.phoenixcontact.com/us/products/1162417>

Depth	57.55 mm
-------	----------

Cable

Length	2 m
--------	-----

Cable/line

14X0.14 [PVC]

Number of positions	14
Shielded	yes
Cable type	14X0.14 [PVC]
Conductor type	Assembled shielded round cable
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	14x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.70 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	71 mm
Smallest bending radius, movable installation	128 mm
Dynamic load capacity (bending)	Max. bending cycles: 5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
Cable type	Front adapter with splitting cable for two modules

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	0 °C ... 80 °C
Altitude	≤ 2000 m (Above sea level)
Permissible humidity (operation)	0 % ... 95 % (non-condensing)

Approvals

UL data

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter



1162417

<https://www.phoenixcontact.com/us/products/1162417>

Altitude	≤ 2000 m
Ambient temperature (operation)	0 °C ... 60 °C
Max. permissible relative humidity (operation)	≤ 95 %

Standards and regulations

Standards/regulations	UL 61010-2-201
-----------------------	----------------

Mounting


Thread type	()
-------------	----

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

Drawings

Circuit diagram



1162417

<https://www.phoenixcontact.com/us/products/1162417>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1162417>



UL Classified
Approval ID: E238705



cUL Classified
Approval ID: E238705



cUL Recognized
Approval ID: E196811



UL Recognized
Approval ID: E196811

cULus Classified

cULus Recognized

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter



1162417

<https://www.phoenixcontact.com/us/products/1162417>

Classifications

ECLASS

ECLASS-11.0	27242292
ECLASS-12.0	27242292
ECLASS-13.0	27242292

ETIM

ETIM 9.0	EC002584
----------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	5175bb3f-02f5-4b84-9357-36f9e680982a

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter



1162417

<https://www.phoenixcontact.com/us/products/1162417>

Accessories

VIP-2/SC/FLK14/PLC - Passive module

2315214

<https://www.phoenixcontact.com/us/products/2315214>

VARIOFACE interface module for 8 channels



VIP-2/PT/FLK14/PLC - Passive module

2903801

<https://www.phoenixcontact.com/us/products/2903801>

VARIOFACE interface module, with push-in connection for 8 channels



VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter

1162417

<https://www.phoenixcontact.com/us/products/1162417>



VIP-2/SC/FLK14/8M/PLC - Passive module

2322281

<https://www.phoenixcontact.com/us/products/2322281>



VARIOFACE interface module, for 8 channels, each with an additional terminal block per signal for a common minus potential

VIP-2/PT/FLK14/8M/PLC - Passive module

2904283

<https://www.phoenixcontact.com/us/products/2904283>



VARIOFACE interface module, with push-in connection, for 8 channels, each with an additional terminal block per signal for a common minus potential

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter

1162417


<https://www.phoenixcontact.com/us/products/1162417>



FLKM 14/KDS3-MT/PPA/PLC - Passive module

2290423

<https://www.phoenixcontact.com/us/products/2290423>



VARIOFACE interface module, for 8 channels with knife disconnect terminal blocks and test sockets to the peripherals and the system

KME - Cable marker carrier

0807083

<https://www.phoenixcontact.com/us/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 x 8 mm

VIP-PA-2X14/26/ 2,0M/1756/064 - Front adapter

1162417

<https://www.phoenixcontact.com/us/products/1162417>



SF-SL 1,0X5,5-150 - Screwdriver

1212552

<https://www.phoenixcontact.com/us/products/1212552>



Screwdriver, bladed (lasered), size: 1.0 x 5.5 x 150 mm, 2-component grip, with non-slip grip

ZBF10:UNBEDRUCKT - Zack Marker strip, flat

0809997

<https://www.phoenixcontact.com/us/products/0809997>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: latching, for terminal block width: 10 mm, lettering field size: 5.15 x 10 mm, Number of individual labels: 10

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com