




Part Number : [877159205](#)
Product Description : 1.00mm Pitch, PCI Express Connector, 98 Circuits, Nylon 4/6 Glass-filled, Black Housing, Phosphor Bronze, 0.38µm Gold Solder-tail, Lead-Free
Series Number : [87715](#)
Status : Active
Product Category : [Card Edge Connectors](#)



Documents & Resources

Drawings

[Drawing 877159205_sd.pdf](#)
[Packaging Design Drawing PK-87715-207-001.pdf](#)

3D Models and Design Files


[3D Model 877159205_stp.zip](#)
[Electrical Model Document EE-87715-004-001.pdf](#)
[Electrical Model Document EE-87715-011-001.pdf](#)
[Electrical Model Document EE-87715-012-001.pdf](#)
[Electrical Model Document EE-87715-013-001.pdf](#)
[Electrical Model Document EE-87715-014-001.pdf](#)
[S-Parameter Model SP-87715-014-001.zip](#)
[S-Parameter Model SP-87715-013-001.zip](#)
[S-Parameter Model SP-87715-004-001.zip](#)
[S-Parameter Model SP-87715-012-001.zip](#)
[S-Parameter Model SP-87715-011-001.zip](#)

Specifications

[Product Specification PS-87715-200-001.pdf](#)
[Test Summary TS-87715-207-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21

REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Card Edge Connectors
Series	87715
Description	1.00mm Pitch, PCI Express Connector, 98 Circuits, Nylon 4/6 Glass-filled, Black Housing, Phosphor Bronze, 0.38µm Gold Solder-tail, Lead-Free
Comments	PCI 8 lanes
Component Type	Edge-card to PCB
Product Family	PCIe PCI-X Connectors
Product Name	PCI Express
Standard Based	PCIe
UPC	822348679904

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	1.1A
-------------------------------	------

Data Rate	8.0 Gbps
High Power Bay (30.0A or more)	No
Voltage - Maximum	50V AC (RMS)/DC

Physical

Circuit Size Range	65-200 Circuits
Circuits (Loaded)	98
Circuits (maximum)	98
Durability (mating cycles max)	50
Edge Card Thickness	1.57mm
Entry Angle	Vertical (Top Entry)
Flammability	94V-0
Keying to Mating Part	Yes
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Net Weight	5.467/g
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	3.00mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	2.40mm
Pitch - Mating Interface	1.00mm
Pitch - Termination Interface	1.00mm
Plating min - Mating	0.381µm
Polarized to Mating Part	Yes
(p)ower-(s)ignal Configuration	98s - 0p
Temperature Range - Operating	-55° to +85°C
Termination Interface Style	Through Hole

Solder Process Data

Max-Duration	10
Lead-Free Process Capability	REFLOW
Max-Cycle	1
Max-Temp	260

Mates With / Use With

Mates with Part(s)

Description	Part Number
Mates With	PCI Express Card