Active

Number of Positions 3

Number of Rows 1

Housing Material **Nylon 6/6**

No documentation available.

Please review product documents or contact us for the latest agency approval information.

Product Type Features	Connector System	Wire-to-Pane
	Connector Style	Receptacle
	Sealed	No
	Applies To	Panel, Wire/
	Product Type	Connector
	Connector Type	Housing
Configuration Features	Number of Positions	3
	Number of Rows	1
	Selectively Loaded	No
	Preloaded	No
Electrical Characteristics	Operating Voltage (VAC)	300
Body Features	Sealable	No
Contact Features	Contact Type	Tab

	Height	26.1 mm [1.0
	Width (mm)	9.4
Usage Conditions	Operating Temperature Range	-30 – 105 °C
Operation/Application	Assembly Integration Feature	Without
Identification Marking	Circuit Identification Feature	Without
Industry Standards	CSA Rating	Certified
	CSA File Number	LR7189
	UL Rating	Recognized
	CSA Certified	Yes
	VDE Tested	Yes
	UL File Number	E28476
Packaging Features	Packaging Quantity	150
	Packaging Method	Bag
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	
	THE TROBUST COM LIMITOR	