

You are here: [Products](#) » [Connectors f.con](#) » [PCB connectors](#) » [Male headers](#) » [SL 2 ... / SL 22 ...](#) »



► Heatsinks f.cool

► Cases f.case

▼ Connectors f.con

► Sockets

▼ PCB connectors

■ Male headers

■ Female headers

■ Direct female connectors

■ Jumpers

► IDC-connectors

► D-Sub connectors

■ Brackets for PC

► Optoelectronics

Male headers

SL 2 ... / SL 22 ...

SL 2 025 12 S

two rows, □ 0.635 mm

add to request



Features

Technical Drawing

Variants

Service

Accessories / related products

Article 1-10 of 17

1 | 2 > >>

Number per page: 10

Picture

Name



►Female headers / BL 2 ...
Stamped contact spring (fork contact), for □ 0...



►Female headers / BL 4 ...
Stamped contact spring (fork contact), for □ 0...



►Female headers / BL LP 2 ...
for □ 0.635 mm



►Female headers / BL LP 4 ...
for square 0.635 mm, packing in a bar magazine (min. 4 contacts)



►Female headers / BL 12 ...
for □ 0.635 mm, can be put through from above and below



►Female headers / BL 21 ...
□ 0.635 mm, can be put through from above



►Female headers / BL 6 ...
for □ 0.635 mm and up to 0.85 mm Ø



►Female headers / BL 8 ...
for □ 0.635 mm and up to 0.85 mm Ø, packing (option) bar magazine



►Female headers / MK 221 ...
□ 0.635 mm and up to 0.85 mm Ø; No capillary action when soldering due to protected contact insert...



►Female headers / BL 10 ...
□ 0.635 mm and up to 0.85 mm Ø, with aligned contact pin

Article 1-10 of 17

1 | 2 > >>