



Part Number : 1553119004

Series Number : 155311  
Product Category : Industrial Cable

Product Description : Flamar Feedback Cable, PVC Jacket, Braided Shielding Overall, 8 Circuits, 3x(2x0.14mm<sup>2</sup> with Spiral Shield) + 2x(0.50mm<sup>2</sup> with Spiral Shield) / 3x(2x26 AWG with Spiral Shield) + 2x(21 AWG with Spiral Shield), 9.00mm (.354") Diameter, 200.0m (656.17') Length, Green  
Status : Obsolete  
Engineering Number : 1X200M

Documents & Resources

Product Environment Compliance

Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Obsolete
Category	Industrial Cable

Series	155311
Description	Flamar Feedback Cable, PVC Jacket, Braided Shielding Overall, 8 Circuits, 3x(2x0.14mm <sup>2</sup> with Spiral Shield) + 2x(0.50mm <sup>2</sup> with Spiral Shield) / 3x(2x26 AWG with Spiral Shield) + 2x(21 AWG with Spiral Shield), 9.00mm (.354") Diameter, 200.0m (656.17') Length, Green
Geographic Area	Global
Product Family	Flamar Standard and Custom Cables for Industrial Automation
Product Name	Flamar,Servo Motor
UPC	889056460149

## Electrical

Current - Maximum per Contact	Contact Molex
Voltage - Maximum	1000V

## Physical

Bending Radius - Minimum	> 15xOD
Cable Length	200.0m
Circuits (Loaded)	8 (6+2)
Color - Cable Jacket	Green
Insulation	TPE
Material - Outer Jacket	PVC
Net Weight	0.010/g
Outer Jacket Diameter	9.00mm
Packaging Type	Reel
Temperature Range - Operating	+5° to +80°C
Wire/Cable Type	UL AWM 2570 / CSA
Wire Size (AWG)	21, 26
Wire Size mm <sup>2</sup>	0.14, 0.50