

CHAMP

TE Internal #: 6339447-7

Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in] Centerline, 2 Row, Standard Profile, Right Angle, PCB Mount

Retention, PCB D-Sub Connectors

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Shielded Receptacle Assembly: Right Angle, 2.16mm











Connector & Housing Type: Receptacle

Connector System: Cable-to-Board

Number of Positions: 50

Centerline (Pitch): 2.16 mm [.085 in]

Number of Rows: 2

All D-Sub Shielded Receptacle Assembly: Right Angle, 2.16mm (20)

Features

Product Type Features

Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Foatures	

Configuration Features

Number of Positions	50
Number of Rows	2
PCB Mount Orientation	Right Angle

Body Features

Assembly Process Feature Material	Carbon Steel
Shield Plating Finish	Bright
Shield Plating Material	Nickel
Shield Material	Copper-Zinc Alloy



Connector Profile	Standard
Contact Features	
Contact Options	Installed
	30 μin
Contact Mating Area Plating Material	Gold
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	3.5 A
Termination Features	
Rectangular Termination Post & Tail Thickness	.25 mm[.01 in]
Rectangular Termination Post & Tail Width	.5 mm[.019 in]
Termination Post & Tail Length	2.29 mm[.09 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Assembly Process Feature Plating Material	Tin
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention	With
Mating Retention Type	4-40 Tapped Holes
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyester GF
Centerline (Pitch)	2.16 mm[.085 in]
Dimensions	
Panel Thickness (Recommended)	1.57 mm[.062 in]
	.062 in
Row-to-Row Spacing	4.3 mm[.169 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Shielded	Yes
Circuit Application	Signal



Packaging Features

Packaging Quantity	40
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





TE Part #1-406541-1 MJ,INV,1X1,6PNL G,.100"ST,SN



TE Part #1-5406203-2 MJ,ASSY,4P,8POS,CAT5,PNL TABS,.1S



TE Part #2143154-2 IMP100S,H,V5P14C,LG,REW39,4.9





MBXLE R/A RCPT,A/C PASS THRU 4ACP+12S+3P

TE Part #1367627-8 light pipe assy, 1x1 sfp

TE Part #2016733-1 RF CA,MCX-RA TO UMCC GEN1, WITH 1.37

TE Part #2159942-1 CA POWER CORDE

TE Part #5-2267775-5 03 MODII HDR SR SFMT B/A T&R, lead-Free

TE Part #6-1775855-4 RJ45 OVER USB W/ LED G/Y 50u" Au

Documents

Product Drawings

RCPT ASSY,LP,SHLD,RA50,STD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6339447-7_B.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_6339447-7_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6339447-7_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Receptacle, Cable-to-Board, 50 Position, 2.16 mm [.085 in] Centerline, 2 Row, Standard Profile, Right Angle, PCB Mount Retention, PCB D-Sub Connectors



Application Specification

English

Agency Approvals

UL

English