



Part Number : 444990112

Series Number : 44499

Product Category : PCB Headers and Receptacles

Product Description : Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Right-Angle, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold(Au) Plating

Status : Active

Documents & Resources

Drawings

- [Drawing 444990112_sd.pdf](#)
- [Packaging Design Drawing PK-42404-002-001.pdf](#)

3D Models and Design Files

- [3D Model 444990112_stp.zip](#)

Specifications

- [Product Specification 55560002-PS-CH-000.pdf](#)
- [Product Specification 55560002-PS-ES-000.pdf](#)
- [Product Specification 55560002-PS-SK-000.pdf](#)
- [Product Specification PS-5556-002-001.pdf](#)
- [Test Summary TS-42404-001-001.pdf](#)
- [Test Summary TS-5556-002-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	44499
Description	Mini-Fit BMI Header, 4.20mm Pitch, Dual Row, Right-Angle, 24 Circuits, PA Polyamide Nylon 6/6, UL 94V-0, with Select Gold(Au) Plating
Application	Board-to-Board, Power, Wire-to-Board
Component Type	PCB Header
Product Family	Mini-Fit Family Power Connectors
Product Name	Mini-Fit BMI
UPC	884982913363

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	9.0A
Voltage - Maximum	600V AC (RMS)

Physical

Breakaway	No
Circuits (Loaded)	24
Circuits (maximum)	24
Color - Resin	Natural

Durability (mating cycles max)	30
First Mate / Last Break	Yes
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Nylon
Net Weight	9.324/g
Number of Rows	2
Orientation	Right Angle
Packaging Type	Tray
PC Tail Length	3.30mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.80mm
Pitch - Mating Interface	4.20mm
Plating min - Mating	2.540µm
Plating min - Termination	1.270µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Partial
Stackable	No
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Through Hole

Solder Process Data

Max-Duration	5
Lead-Free Process Capability	WAVE
Max-Cycle	1
Max-Temp	240

Mates With / Use With

Mates with Part(s)

Description	Part Number
Mini-Fit BMI Vertical Dual Row Receptacle Headers	<u>42385</u>
Mini-Fit BMI Dual Row Receptacle Housings	<u>42474</u>
Mini-Fit BMI Dual Row Receptacle Housings	<u>44516</u>
Mini-Fit Jr. Receptacle Housings	<u>5557</u>