





1		2		3		4		5		6		7		8			
SAMZO		REAC/ROHS								REV	ECN NO	DESRIPTION	DESIGN	APPROVAL	DATE		
										A1	NEW	Replace frame			2013.02.12		
E	技术要求: Technical requirements: 1.打铜底0.5-1UM,镍底2-2.5UM,亮锡3-5UM。 Copper base 0.5 - 1 UM, nickel base 2 - 2.5 UM, bright tin 3 - 5 UM. 2.不得有脚变形, 毛刺等缺陷。 There shall be no defects such as pin deformation and burrs. 3.插脚尖部符合可焊性要求。 The tip of the insertion pin shall meet the solderability requirements. 4.螺纹需符合通止规要求。 The thread shall meet the requirements of the go and no-go gauge. 5.材质: 紫铜T2。 Material: Red copper T2. 6.过载电流: 240A Overload current: 240A 7.牙孔规格 M6 The specification of the threaded hole M6 8.未标注尺寸公差值按GB/T1184-1996H级 Unmarked dimensional tolerance values are in accordance with Grade H of GB/T1184-1996 9.螺丝扭力: 3.0Nm Screw torque: 3.0Nm 10.盐雾试验: 48小时 Salt spray test: 48H																
D																	
C																	
B	182016040TD6 Pressing hole specification: M6 Mold number: CS094 Pin height:4.0mm Height above the board: 16.0mm Specification size: 18*20mm 																
A	ITEM	DESCRIPTION	MATERIAL	QTY	FINSH/COLOR												
	A	Subject	Red copper T2	1	tin plating												
	B	Gasket	H62(Y2)	1	tin plating												
	F																
										FIRST VIEW				The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM		TITLE::	
																18*20*20mm	
										SCALE1:1UNITmm						DWG NO: 1820C-P094	
																PART NO: 1820C-139010	
										SAMZO COMPONENTS				MODEL NO: 182016040TD6			
										Electronic switch and connector manufacturer				NAME:		PCB soldering terminal	
1		2		3		4		5		6		7		8			