





MSCSM120TLM11CAG

Three Level Inverter SiC MOSFET Power Module

Product Overview

The MSCSM120TLM11CAG device is a three level inverter 1200V/251A silicon carbide (SiC) MOSFET power module.



Note: All ratings at $T_J = 25^\circ\text{C}$, unless otherwise specified.



These devices are sensitive to electrostatic discharge. Proper handling procedures must be followed.

Features

The following are key features of the MSCSM120TLM11CAG device:

- SiC Power MOSFET
 - Low $R_{DS(on)}$
 - High temperature performance
- SiC Schottky Diode
 - Zero reverse recovery
 - Zero forward recovery
 - Temperature independent switching behavior
 - Positive temperature coefficient on VF
- Low stray inductance
- Kelvin source for easy drive
- M5 power connectors
- High level of integration
- Aluminum nitride (AlN) substrate for improved thermal performance

Benefits

The following are the benefits of MSCSM120TLM11CAG device:

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction-to-case thermal resistance
- Low profile
- RoHS Compliant

Application

The MSCSM120TLM11CAG device is designed for the following applications:

- Solar converter
- Uninterruptible power supplies

Electrical Specifications

This section provides the electrical specifications of the MSCSM120TLM11CAG device.

SiC MOSFET Characteristics (Per SiC MOSFET)

The following table lists the absolute maximum ratings per SiC MOSFET of the MSCSM120TLM11CAG device.

Table 1. Absolute Maximum Ratings

Symbol	Parameter	Maximum Ratings		Unit
V_{DSS}	Drain-Source voltage	1200		V
I_D	Continuous drain current	$T_C = 25^\circ\text{C}$	251	A
		$T_C = 80^\circ\text{C}$	200	
I_{DM}	Pulsed drain current	500		
V_{GS}	Gate-Source voltage	−10/25		V
$R_{DS(on)}$	Drain-Source ON resistance	10.4		$\text{m}\Omega$
P_D	Power dissipation	$T_C = 25^\circ\text{C}$	1042	W

The following table lists the electrical characteristics per SiC MOSFET of the MSCSM120TLM11CAG device.

Table 2. Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min.	Typ.	Max.	Unit
I_{DSS}	Zero gate voltage drain current	$V_{GS} = 0\text{V}; V_{DS} = 1200\text{V}$		—	30	300	μA
$R_{DS(on)}$	Drain-Source on resistance	$V_{GS} = 20\text{V}$	$T_J = 25^\circ\text{C}$	—	8.3	10.4	$\text{m}\Omega$
		$I_D = 120\text{A}$	$T_J = 175^\circ\text{C}$	—	13.3	—	
$V_{GS(th)}$	Gate threshold voltage	$V_{GS} = V_{DS}; I_D = 3\text{ mA}$		1.8	2.8	—	V
I_{GSS}	Gate-Source leakage current	$V_{GS} = 20\text{V}; V_{DS} = 0\text{V}$		—	—	300	nA

The following table lists the dynamic characteristics per SiC MOSFET of the MSCSM120TLM11CAG device.

Table 3. Dynamic Characteristics

Symbol	Characteristic	Test Conditions		Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{GS} = 0V$ $V_{DS} = 1000V$ $f = 1\text{ MHz}$		—	9	—	nF
C_{oss}	Output capacitance			—	0.81	—	
C_{rss}	Reverse transfer capacitance			—	0.07	—	
Q_g	Total gate charge	$V_{GS} = -5V/20V$ $V_{Bus} = 800V$ $I_D = 120A$		—	696	—	nC
Q_{gs}	Gate-source charge			—	123	—	
Q_{gd}	Gate-drain charge			—	150	—	
$T_{d(on)}$	Turn-on delay time	$V_{GS} = -5V/20V$ $V_{Bus} = 600V$ $I_D = 150A$ $R_{G(on)} = 2.7\Omega$ $R_{G(off)} = 1.6\Omega$	$T_J = 150\text{ }^{\circ}\text{C}$	—	56	—	ns
T_r	Rise time			—	55	—	
$T_{d(off)}$	Turn-off delay time			—	166	—	
T_f	Fall time			—	67	—	
E_{on}	Turn-on energy	$V_{GS} = -5V/20V$ $V_{Bus} = 600V$ $I_D = 150A$ $R_{G(on)} = 2.7\Omega$ $R_{G(off)} = 1.6\Omega$	$T_J = 150\text{ }^{\circ}\text{C}$	—	3	—	mJ
E_{off}	Turn-off energy			—	2.7	—	
R_{Gint}	Internal gate resistance			—	2	—	
R_{thJC}	Junction-to-case thermal resistance			—	—	0.144	°C/W

The following table lists the body diode ratings and characteristics per SiC MOSFET of the MSCSM120TLM11CAG device.

Table 4. Body Diode Ratings and Characteristics

Symbol	Characteristic	Test Conditions		Min.	Typ.	Max.	Unit
V_{SD}	Diode forward voltage	$V_{GS} = 0V; I_{SD} = 120A$		—	4	—	V
		$V_{GS} = -5V; I_{SD} = 120A$		—	4.2	—	
t_{rr}	Reverse recovery time	$I_{SD} = 120A; V_{GS} = -5V$ $V_R = 800V; dI_F/dt = 3000\text{ A}/\mu\text{s}$		—	90	—	ns
Q_{rr}	Reverse recovery charge			—	1650	—	
I_{rr}	Reverse recovery current			—	41	—	

CR1 and CR2 SiC Diode Ratings and Characteristics (Per SiC Diode)

The following table lists the CR1 and CR2 SiC diode ratings and characteristics per SiC diode of MSCSM120TLM11CAG device.

Table 5. SiC Schottky Diode Ratings and Characteristics

Symbol	Characteristic	Test Conditions		Min.	Typ.	Max.	Unit
V_{RRM}	Peak repetitive reverse voltage			—	—	1200	V
I_{RRM}	Reverse leakage current	$V_R = 1200V$	$T_J = 25^\circ C$	—	45	600	μA
			$T_J = 175^\circ C$	—	750	—	
I_F	DC forward current	—	$T_C = 100^\circ C$	—	150	—	A
V_F	Diode forward voltage	$I_F = 150A$	$T_J = 25^\circ C$	—	1.5	1.8	V
			$T_J = 175^\circ C$	—	2.1	—	
Q_C	Total capacitive charge	$V_R = 600V$		—	672	—	nC
C	Total capacitance	$f = 1 \text{ MHz}, V_R = 400V$		—	738	—	pF
		$f = 1 \text{ MHz}, V_R = 800V$		—	546	—	
R_{thJC}	Junction-to-case thermal resistance			—	—	0.212	$^\circ C/W$

Thermal and Package Characteristics

The following table lists the thermal and package characteristics of the MSCSM120TLM11CAG device.

Table 6. Thermal and Package Characteristics

Symbol	Characteristics	Min.	Max.	Unit
V_{ISOL}	RMS isolation voltage, any terminal to case t =1 min, 50 Hz/60 Hz	4000	—	V
T_J	Operating junction temperature range	-40	175	$^\circ C$
T_{JOP}	Recommended junction temperature under switching conditions	-40	$T_{Jmax}-25$	
T_{STG}	Storage temperature range	-40	125	
T_c	Operating case temperature	-40	125	
Torque	Mounting torque	To heatsink	M6	3
		For terminals	M5	2
Wt	Package weight	—	300	g

Typical SiC MOSFET Performance Curve

This section shows the typical SiC MOSFET performance curves of the MSCSM120TLM11CAG device.

Figure 1. Maximum Thermal Impedance




Figure 2. Output Characteristics, $T_J = 25^{\circ}\text{C}$




Figure 3. Output Characteristics, $T_J = 175^{\circ}\text{C}$








Figure 4. Normalized $R_{DS(on)}$ vs. Temperature**Figure 5. Transfer Characteristics****Figure 6. Switching Energy vs. R_g** **Figure 7. Switching Energy vs. Current**

Figure 8. Capacitance vs. Drain Source Voltage




Figure 9. Gate Charge vs. Gate Source Voltage







Figure 10. Body Diode Characteristics, $T_J = 25^\circ C$ Figure 11. 3rd Quadrant Characteristics, $T_J = 25^\circ C$ 

Figure 12. Body Diode Characteristics, $T_J = 175^\circ\text{C}$ **Figure 13. 3rd Quadrant Characteristics, $T_J = 175^\circ\text{C}$** **Figure 14. Operating Frequency vs Drain Current**

Typical SiC Diode Performance Curves

This section shows the typical SiC diode performance curves of the MSCSM120TLM11CAG device.

Figure 15. Maximum Thermal Impedance




Figure 16. Forward Characteristics





Figure 17. Capacitance vs. Reverse Voltage




Package Specifications

The following section shows the package specification of the MSCSM120TLM11CAG device.

Package Outline

The following figure shows the package outline drawing of the MSCSM120TLM11CAG device. The dimensions in the following figure are in millimeters.

Figure 18. Package Outline Drawing



Revision History

Revision	Date	Description
A	12/2021	This is the first publication of this document.

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable". Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzers, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Parallelizing, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVM Express, NVMe, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2021, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-5224-9523-9

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.



MICROCHIP

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: www.microchip.com/support Web Address: www.microchip.com	Australia - Sydney Tel: 61-2-9868-6733 China - Beijing Tel: 86-10-8569-7000 China - Chengdu Tel: 86-28-8665-5511 China - Chongqing Tel: 86-23-8980-9588 China - Dongguan Tel: 86-769-8702-9880 China - Guangzhou Tel: 86-20-8755-8029 China - Hangzhou Tel: 86-571-8792-8115 China - Hong Kong SAR Tel: 852-2943-5100 China - Nanjing Tel: 86-25-8473-2460 China - Qingdao Tel: 86-532-8502-7355 China - Shanghai Tel: 86-21-3326-8000 China - Shenyang Tel: 86-24-2334-2829 China - Shenzhen Tel: 86-755-8864-2200 China - Suzhou Tel: 86-186-6233-1526 China - Wuhan Tel: 86-27-5980-5300 China - Xian Tel: 86-29-8833-7252 China - Xiamen Tel: 86-592-2388138 China - Zhuhai Tel: 86-756-3210040	India - Bangalore Tel: 91-80-3090-4444 India - New Delhi Tel: 91-11-4160-8631 India - Pune Tel: 91-20-4121-0141 Japan - Osaka Tel: 81-6-6152-7160 Japan - Tokyo Tel: 81-3-6880- 3770 Korea - Daegu Tel: 82-53-744-4301 Korea - Seoul Tel: 82-2-554-7200 Malaysia - Kuala Lumpur Tel: 60-3-7651-7906 Malaysia - Penang Tel: 60-4-227-8870 Philippines - Manila Tel: 63-2-634-9065 Singapore Tel: 65-6334-8870 Taiwan - Hsin Chu Tel: 886-3-577-8366 Taiwan - Kaohsiung Tel: 886-7-213-7830 Taiwan - Taipei Tel: 886-2-2508-8600 Thailand - Bangkok Tel: 66-2-694-1351 Vietnam - Ho Chi Minh Tel: 84-28-5448-2100	Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393 Denmark - Copenhagen Tel: 45-4485-5910 Fax: 45-4485-2829 Finland - Espoo Tel: 358-9-4520-820 France - Paris Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 Germany - Garching Tel: 49-8931-9700 Germany - Haan Tel: 49-2129-3766400 Germany - Heilbronn Tel: 49-7131-72400 Germany - Karlsruhe Tel: 49-721-625370 Germany - Munich Tel: 49-89-627-144-0 Fax: 49-89-627-144-44 Germany - Rosenheim Tel: 49-8031-354-560 Israel - Ra'anana Tel: 972-9-744-7705 Italy - Milan Tel: 39-0331-742611 Fax: 39-0331-466781 Italy - Padova Tel: 39-049-7625286 Netherlands - Drunen Tel: 31-416-690399 Fax: 31-416-690340 Norway - Trondheim Tel: 47-72884388 Poland - Warsaw Tel: 48-22-3325737 Romania - Bucharest Tel: 40-21-407-87-50 Spain - Madrid Tel: 34-91-708-08-90 Fax: 34-91-708-08-91 Sweden - Gothenberg Tel: 46-31-704-60-40 Sweden - Stockholm Tel: 46-8-5090-4654 UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820