



Fittings with swivel external thread

- HG-45M 45° Elbow Swivel External Thread, IP66

45° elbow swivel brass external thread.

Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus




Helaguard HG-45M 45° Elbow Swivel External Thread, IP66.

MATERIAL	Polyamide 6.6 (PA66), Nickel Plated Brass (NPB)
Operating Temperature	-50 °C to +135 °C
Flammability	UL94 V2
Specifications	UL-Recognised

HF ✓

RoHS ✓



Helaguard fitting, 45° with swivel external thread

TYPE	Nominal Ø	Thread Size	Min. Bore Size (B)	Outside Ø max (OD max.)	Length (L)	A/F Thread (A/F2)	Thread Length (TL)	Pack Cont.	Colour	Article-No.
HG16-45M-M20	16	M20	14.0	29	69	24	12	10 pcs.	Black (BK)	166-23700
HG16-45M-PG13	16	PG13.5	14.0	29	67	24	10	10 pcs.	Black (BK)	166-23706
HG16-45M-PG16	16	PG16	14.0	29	70	29	13	10 pcs.	Black (BK)	166-23707
HG21-45M-M20	21	M20	14.0	32	76	24	12	10 pcs.	Black (BK)	166-23701
HG21-45M-PG13	21	PG13.5	14.0	32	74	24	10	10 pcs.	Black (BK)	166-23708
HG21-45M-PG16	21	PG16	14.0	32	77	29	13	10 pcs.	Black (BK)	166-23709
HG28-45M-M25	28	M25	19.0	44	90	29	12	10 pcs.	Black (BK)	166-23702
HG28-45M-PG21	28	PG21	19.0	44	92	35	14	10 pcs.	Black (BK)	166-23710
HG34-45M-M32	34	M32	24.5	51	98	38	13	10 pcs.	Black (BK)	166-23703
HG34-45M-PG29	34	PG29	24.5	51	99	42	14	10 pcs.	Black (BK)	166-23711
HG42-45M-M50	42	M50	39.0	63	117	58	17	2 pcs.	Black (BK)	166-23704
HG54-45M-M50	54	M50	39.0	76	137	58	17	2 pcs.	Black (BK)	166-23705

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval.