



| REVISIONS | | | | | |
|-----------|-----|-------------------------|-----------|-----|------|
| P | LTR | DESCRIPTION | DATE | DWN | APVD |
| | DI | DELETE NOTE 5 | - | - | - |
| | E | .240/.220 WAS .210 MIN | 29JUN2007 | TL | TL |
| | F | UPDATE CAV #6 TO MOLDED | 02DEC2008 | TL | TL |
| | G | REV PER ECN-22-174104 | 14SEP2022 | LN | AE |

- NOTES:
- 1 INSULATOR: GLASS FILLED (PPS). COLOR:BLACK
 - 2 EPOXY ENCAPSULATION. EPOXY MAY WICK .035 MAX
 - 3 CONNECTOR SHALL BE MARKED ON BOTH SIDES. MARKING SHALL CONTAIN: TE & MICRODOT LOGO, CAGE CODE (98278), TE PART NUMBER (1532026-2) & DATE CODE (YYWW). POSITION 1 SHALL ALSO BE MARKED.
 - 4 CHAMFER OF SOLDER POT TO BE PARALLEL TO THE SIDES OF CONNECTOR WITHIN 10°.
 - 5 CAVITY #6 IS NOT POPULATED. EPOXY ENCAPSULATION AS SHOWN.

| | | | | | |
|--|--|---------------------------------|---|-----------|------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN N. LOHITH 19AUG2022 | <div>TE Connectivity</div> <div>STRIP CONNECTOR MCSARX-15PS</div> | | |
| DIMENSIONS: in | TOLERANCES UNLESS OTHERWISE SPECIFIED: | CHK E. ALBERTO 19AUG2022 | | | |
| | | APVD E. ALBERTO 19AUG2022 | | | |
| | | PRODUCT SPEC | | | |
| | 0 PLC ±- | APPLICATION SPEC | NAME | | |
| | 1 PLC ±.1 | - | SIZE | CAGE CODE | DRAWING NO |
| MATERIAL | 2 PLC ±.01 | WEIGHT | A3 | 98278 | 1532026-2 |
| | 3 PLC ±.001 | CUSTOMER DRAWING | SCALE 8:1 | | |
| - | 4 PLC ±.0001 | | SHEET 1 OF 1 | | |
| - | ANGLES ±- | | REV G | | |
| | FINISH | | | | |
| | - | | | | |
| | - | | | | |