

D款, 反向10.0四脚, DIP-*6.50

MAPX

MODIFICATION






DATE

NOTES:

1. HOUSING: SEE NOTES, UL94V-0 .
TERMINAL: SEE NOTES.
SHELL: SEE NOTES.

SPECIFICATION:

1. ELECTRICAL CHARACTERISTIC:
CONTACT RESISTANCE: $30m\Omega$ MAX
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
INSULATION RESISTANCE: $1000M\Omega$ MIN
2. MECHANICAL CHARACTERISTIC:
INSERTION FORCE: 35N(3.57KGF) MAX
EXTRACTION FORCE: $10\sim35N(1.02\sim3.57KGF)$ MIN
DURABILITY: 1500 CYCLES EXTRACTION FORCE: $10\sim35N$
5000 CYCLES MIN
5000 CYCLES EXTRACTION FORCE: $3\sim35N$
3. ENVIRONMENTAL:
OPERATING TEMPERATURE: $-55^{\circ}C+85^{\circ}C$
4. Contact finish:
01:Selective Gold Flash
02:Selective Gold 3U"
03:Selective Gold 5U"
04:Selective Gold 15U"
05:Selective Gold 30U"



产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.15	X.	±5.°
.X	±0.10	.X	±2.°
.XX	±0.05	.XX	±1.°
.XXX	±0.03	.XXX	±0.5°

深圳市精拓金电子有限公司

单位

MM

制图

Z-Y-B

制图料号

911-321B1017D10100

比例

1:1

审核

产品名称

AF10.0D款四脚无边方弹壳反向
PBT白胶6.5DIP

日期

2012.09.24

核准

角法

版本

AD