




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Right Angle**

Connector System: **Board-to-Board**

Number of Positions: **2**

Number of Rows: **1**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Stackable	Yes
PCB Mount Orientation	Right Angle
Number of Positions	2
Number of Rows	1

Body Features

Connector Profile	Standard
Primary Product Color	Black

Contact Features

Contact Protection Type	Closed Entry Housing
-------------------------	----------------------



Mating Square Post Dimension	.63 mm[.024 in]
PCB Contact Termination Area Plating Material Thickness	2.5 µm
Mating Pin Diameter	.63 mm[.024 in]
PCB Contact Termination Area Plating Material Finish	Matte
Contact Shape & Form	Square
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.762 µm[30 µin]
Contact Type	Socket
Contact Current Rating (Max)	3 A

Termination Features

Rectangular Termination Post & Tail Thickness	.2 mm[.008 in]
Rectangular Termination Post & Tail Width	.69 mm[.027 in]
Termination Post & Tail Length	3.2 mm[.126 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment	Without
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Side
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Polyester - GF

Dimensions

Connector Height	3.2 mm[.126 in]
Row-to-Row Spacing	7.62 mm[.3 in]
PCB Thickness (Recommended)	1.6 mm[.062 in]

Usage Conditions

Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
-----------------------------	----------------------------

Operation/Application



Solder Process Feature	Board Standoff
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	400
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





TE Part # 826629-2
2P AMPMODU II



TE Part # 826646-2
AMPMODU II R/A HEADER



TE Part # 826631-2
2P AMPMODU II PIN HEADER



TE Part # 826630-2
2P AMPMODU II STIFT LEI



TE Part # 826652-2
2P AMPMODU II STIFT LEI



TE Part # 826647-2
2P AMPMODU II STIFT LEI



TE Part # 826648-2
2P AMPMODU II STIFT LEI




TE Part # 215267-2
AMPMODU, BREAK-AWAY



TE Part # 826655-2
2P AMPMODU II STIFT LEI

Also in the Series

AMPMODU HV-100/HV-190




PCB Headers & Receptacles(333)

Customers Also Bought



TE Part #350834-1
06P UMNL HDR ASSY PC 94VO



TE Part #1775316-3
HPI, 2.5MM PITCH, R/A, SMT TYPE, 3POS



TE Part #2-1969688-4
PTL 1X4 PCB HEADER VERT HITEMP KEY B RED



TE Part #3-644767-6
06P MTA156 HDR ASSY FL ST LF



TE Part #4-1546108-4
EUROSTYLE TB, PLUG, GREY, STKG 8P

TE Part #6-2176452-5
CPF 0201 2K49 0.1% 25ppm 1K RL

TE Part #6-2176452-6
CPF 0201 2K55 0.1% 25ppm 1K RL

TE Part #8-2176452-9
CPF 0201 4K42 0.1% 25ppm 1K RL

TE Part #216398-4
48P.IEC-C MALE CONN

Documents

Product Drawings
2P HV190 FEDERLEIS

English

CAD Files
Customer View Model
ENG_CVM_CVM_216602-2_B.3d_igs.zip
English
Customer View Model
ENG_CVM_CVM_216602-2_B.3d_stp.zip
English
Customer View Model
ENG_CVM_CVM_216602-2_B.2d_dxf.zip
English

3D PDF
3D

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages
1773393_ AMPMODU_EUROPEAN_STANDARD_PRODUCTS
English