Plating		Electro-Tin				
Wire Size		1 AWG				
Wire Type		Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric			.47 R Ref	Color coded barrel markings
Wire Strip Length		15/16 in.				
Stud Size		3/8 in.	.70±.04	→ N S S S S S S S S S S S S S S S S S S		PANDUIT
UL Listed Wire Connector		Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.36±.04	.63±.02	.41±.02 DIA (2) PLS	ORIEN
UL Temperature Rating		90 ° C	_	1.00±.02		
C.S.A Certified Wire Connector		Yes		ļ		
Panduit Color Code on Barrel		GREEN	-	2.99	2±.06 ————————————————————————————————————	
Panduit Die In on Barrel	dex No.	P37				na ——
Alternate Industry Die Index No. () on Barrel		(11)		Wire inspection windo		Beveled widentry
	CERTIFIED	B UL D LISTED	<u> </u>			.36±.01 .47±.01
		Wire Connector	11±.01			
					MOUIT CORP.	TINLEY PARK, ILLINOI
					LCD1-38AI	D-E
00 10/05 JHI	NU JHNU	RELEAS		PC00148 COPP	oer Lug - Two-Hole Slot	ted Standard Rarrel