




SPLICE

TE Internal #: 40509
Pigtail Splice / Thru Splice, Serrated, 3300 – 9000 CMA Wire Size,
Brass, 3 Serration, Length 3.86 mm [.152 in], Reel, Open, SPLICE,
Splices

[View on TE.com >](#)

Terminals & Splices > Splices



Splice Type: **Pigtail Splice, Thru Splice**
Sealable: **No**
Splice Features: **Serrated**
Wire Size: **3300 – 9000 CMA**
Contact Base Material: **Brass**

Features

Product Type Features

Splice Type	Pigtail Splice, Thru Splice
Sealable	No
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support

Configuration Features

Number of Serrations	3
Compatible With Wire & Cable Type	Discrete Wire

Body Features

Product Weight	.143 g[.005 oz]
Splice Features	Serrated

Contact Features

Contact Base Material	Brass
Barrel Type	Open

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Wire Size	3300 – 9000 CMA
Terminal Material Thickness	.51 mm[.02 in]
Product Length	3.86 mm[.152 in]

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Government Qualified Splice	No
-----------------------------	----

Packaging Features

Packaging Quantity	30000
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>






EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent

chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 60806-1 SPLICE IS 1600-4100 .0126 BR	 TE Part # 62759-1 SPLICE 400-1300 .016 BR	 TE Part # 62754-1 SPLICE 14000-30000 .030 BR	 TE Part # 62382-1 SPLICE 25/26 .012 BR
 TE Part # 62516-2 SPLICE IS 1600-4100 .0126 BR	 TE Part # 4150059-1 OCEAN-2.0-APPLICATOR-E-140F-SEM	 TE Part # 7-4150059-7 OCEAN_2.0_SPARE_PART_KIT-140F	 TE Part # 4150059-2 OCEAN-2.0-APPLICATOR-E-140F-SEA


Also in the Series | SPLICE

 Crimp Wire Pins, Tabs & Ferrules(1)	 Splices(64)
--	---

Customers Also Bought



TE Part #1586849-1
03P UMNL CAP HSG NATL, GW



TE Part #1586765-8
8P RCPT VAL-U-LOK GW



TE Part #42617-1
187 FASTON REC 20-16 AWG BR



TE Part #62813-1
250 FASTON FLAG REC 22-18 AWG BR



TE Part #1586851-1
02P UMNL PLUG HSG, GW




TE Part #42400-1
250 FASTON REC 18-14 AWG BR



TE Part #350699-1
UMNL SPLIT PIN PTPBR



TE Part #63477-1
187 FASTON REC 20-16 AWG BR



TE Part #63538-1
250 FASTON FLAG REC 18-14 BR



TE Part #63306-1
250 FASTON REC 18-14 AWG BR

Documents

Product Drawings

SPLICE 3300 TO 9000 CMA BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_40509_BB_c-40509-bb.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_40509_BB_c-40509-bb.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_40509_BB_c-40509-bb.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

English

Agency Approvals

CSA Certificate

English