



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH Strike Housings



Connector System: **Wire-to-Wire**
Number of Positions: **32**
Connector & Housing Type: **Housing for Female Terminals**
Centerline (Pitch): **3.4 mm [.134 in]**
Sealable: **Yes**

[All DEUTSCH Strike Housings \(20\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Number of Positions	32
Number of Rows	4

Electrical Characteristics

Operating Voltage	48 VAC
Nominal Voltage Architecture	48 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black



Connector & Keying Code	A
-------------------------	---

Contact Features

Contact Size	Size 16, Size 20
Contact Type	Socket
Mating Pin Diameter	1 mm, 1.55 mm [.039 in][.061 in]
Contact Current Rating (Max)	7.5 A, 13 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	With
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT
Centerline (Pitch)	3.4 mm [.134 in]

Dimensions

Connector Height	48.5 mm [1.909 in]
Product Width	38.9 mm [1.532 in]
Product Length	81 mm [3.189 in]
Row-to-Row Spacing	10.85 mm, 11.35 mm, 3.5 mm [.138 in][.427 in][.447 in]
Compatible Insulation Diameter Range	1.55 – 2.41 mm, 1.55 – 3.05 mm [.061 – .095 in][.061 – .12 in]

Usage Conditions

Operating Temperature (Max)	125 °C [257 °F]
Operating Temperature Range	-55 – 125 °C [-67 – 257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	Not tested

Packaging Features



Packaging Quantity	144
Packaging Method	Box

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



 TE Part # CAT-D48-SP729 DEUTSCH Sealing Plugs	 TE Part # CAT-J67-DSCC16 DEUTSCH Size 16 Crimp Contacts	 TE Part # CAT-D48-ST273 DEUTSCH Solid Contacts	 TE Part # DT-RT1 EXT TOOL, FRONT RELEASE
 TE Part # 1062-20-0622 SOC, SF, SIZE 20, 14-16, NI/NI	 TE Part # 1062-20-0322 SOC, SF, SIZE 20, 16-22, SLEVLESS, NI/NI	 TE Part # 1062-20-0277 SOC, SF, SIZE 20, 16-22, SN/SN	 TE Part # SRK-BS-MD-ST-001 BKSHL, MED, BLK, ST, NW 17/22
 TE Part # CAT-ST858-H342 DEUTSCH Strike Headers	 TE Part # SRK-BS-MD-90-001 BKSHL, MED, BLK, RA, NW 17/22	 TE Part # 1062-20-0244 SOC, SF, SIZE 20, 16-22, AU/SN	 TE Part # 1062-20-0222 SOC, SF, SIZE 20, 16-22, NI/NI
 TE Part # 1062-20-0122 SOC, SF, SIZE 20, 16-22, NI/NI	 TE Part # 1062-20-0144 SOC, SF, SIZE 20, 16-22, AU/SN	 TE Part # 1062-20-0377 SOC, SF, SIZE 20, 16-22, SLEVLESS, SN/SN	 TE Part # 1062-20-0177 SOC, SF, SIZE 20, 16-22, SN/SN
 TE Part # 1062-20-0344 SOC, SF, SIZE 20, 16-22, SLEVLESS, AU/SN	 TE Part # 1062-20-0644 SOC, SF, SIZE 20, 14-16, AU/SN	 TE Part # 1062-20-0677 SOC, SF, SIZE 20, 14-16, SN/SN	 TE Part # SRK-BS-MD-90-002 BKSHL, MED, BLK, RA, NW 22

Also in the Series | STRIKE



Automotive Housings(20)



PCB Headers & Receptacles(10)

Customers Also Bought




TE Part #SRK06-MDB-32A-001
DEUTSCH Strike Housings



TE Part #2-1564520-1
12POS,TAB 1.6X0.6,TAB HSG,ASSY



TE Part #2-2112162-1
21POS,TAB2.8X0.8,TABHSG,CODE B, ASSY,SLD



TE Part #213847-3
POWERBAND CONT ASSY,SILVER PLT



TE Part #35664
TERMINAL,SOLIS R 8 1/2



TE Part #1-66360-5
III+ SKT,18-14,TIN-LEAD,LP



TE Part #DTSK06-1-08SA
PLUG, INLINE, KEY A



TE Part #0810-201-2401
GROMMET

Documents

Product Drawings

PLG, 32P, BLK, E, A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_SRK06-MDA-32A-001_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_SRK06-MDA-32A-001_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_SRK06-MDA-32A-001_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.



Datasheets & Catalog Pages

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English