




# HTWD Halogen Free Wiring Duct HTWD-HF-100X75

HelaDuct HTWD-HF (DIN sizes), Article number: 183-11075



Images (4)

Downloads



## Features

- Excellent fire-safety characteristics
- Narrow slots suitable for small-diameter wires
- Smooth, burr-free edges protect installers from injury and wires from damage
- Fingers can be removed with no sharp edges at pre-notched snap-off points
- Further pre-notched snap-off point at base of sidewall allow cutting out and removing sections of sidewall with no sharp edges
- Duct covers hold securely even in a vertical position and under vibration
- Cover is flush with side of duct, allowing for tight, contiguous placement of duct
- Base perforation according to DIN EN 50085

## Certifications & Approvals



## Application

HellermannTyton HTWD-HF halogen-free ducts are used wherever there are high demands on personal or material safety, such as public transport, tunnels, lifts and data processing centres.  
Note: Halogen-free PC+ABS is not resistant to all oils and greases.

HelaDuct HTWD-HF (DIN sizes) is suitable for following markets and industries

Electrical Installation

Rail Transportation Sector

Panell Building

## More products in this product group

[HTWD Halogen Free Wiring Duct >](#)

## Base Data





Application Tool	4FTOOL
Colour	Grey RAL 7035 (RAL7035)
Current leak stable Yes/No	Yes
Description Short (BMEcat) (max. 150 characters)	Wiring duct 100x75 mm, 2000 mm, PC/ABS, grey
Fixation Method	Screw Mounting
GLOBAL PART DESCRIPTION	HTWD-HF-100X75-PC/ABS-GY
Pack Cont.	16
Package Quantity per	box
Product Family	HelaDuct HTWD-HF (DIN sizes)

Type of side wall	Slotted
-------------------	---------

## Product Dimensions

Height (H)	75 mm
Length (L)	2 m
Suitable for cross section	6063 mm <sup>2</sup>
Width (W)	100 mm
Width (W2)	5.0 mm
Width (W3)	7.5 mm

## Material and Specifications


ELV compliant (Article 4 - 2)	YES
EN 45545-2 Results	R22 HL2, R23 HL2
Flammability	UL 94 V0
Halogenfree	Yes
Hazardous good	No
Material	Acrylonitrile Butadiene Styrene alloyed with Polycarbonate (PC/ABS)
Operating Temperature - °C	-25 °C to +90 °C, intermittent +100 °C
Specifications	   
Specifications	DIN EN 45545-2 (02/2016), ISO11925, NF F 16-101

## Logistics and Packaging


## More Information


ETIM 5.0	EC000012
ETIM 6.0	EC000012
UNSPSC Key	39131712

## Further information to HTWD-HF-100X75



Technical drawing 10-0777-001-CSG


 Download >



CAD-Download

[Download >](#)

## Competences



## Wiring ducts and accessories from HelaDuct: optimum protection for cables and fitters.

Discover the advantages of HelaDuct wiring ducts system solutions with its special space-saving shapes: these unique wiring ducts are designed for height and give you more lateral space. They come with blunted edges that protect the cable insulation and make them safer to work with during installation and maintenance. HelaDuct products are used in switch cabinets and switching stations and are very well suited to cables with small cross sections.

[Wiring ducts >](#)

## Accessories



**4FTOOL**  
182-96000

## Similar products



**HTWD-HF-25X25**  
183-12525  
HTWD Halogen Free  
Wiring Duct



**HTWD-HF-25X50**  
183-12550  
HTWD Halogen Free  
Wiring Duct



**HTWD-HF-37.5X37.5**  
183-13737  
HTWD Halogen Free  
Wiring Duct



**HTWD-HF-37.5X50**  
183-13750  
HTWD Halogen Free  
Wiring Duct



**HTWD-HF-37.5X75**  
183-13775  
HTWD Halogen Free  
Wiring Duct



**HTWD-HF-50X50**  
183-15050  
HTWD Halogen Free  
Wiring Duct

[Show all ▾](#)

## Stay in touch with us!



### Global Company

About us  
Worldwide  
Philosophy  
Environment & Quality  
Corporate Social  
Responsibility  
Product Development  
E-Business  
ACADEMY  
Careers  
MADE FOR REAL

### Products

Product overview  
Cable Ties and Fixings  
Insulation  
Cable Protection Systems  
Electrical Installation  
Identification Systems  
Application Tooling  
Connectivity

### Competences

Cable Ties  
Heat Shrink Tubing  
Industrial Identification  
and Self-Adhesive Labels  
Cable Protection  
Conduits  
Electrical Installation  
Electrical tape  
Wire connectors  
Cable rods  
Downlight covers  
Cable jointing  
Gel-filled cable joints  
Cable Tie Guns  
Connectivity Products  
RFID tracking  
Cable tie mounts  
Thermal Transfer Printer  
P-Clamp  
Wiring ducts

### Markets & Industries

Automotive Industry  
Solar plants  
Wind turbines  
Shipbuilding  
Panel building  
Rail industry  
Food Industry  
Chemical Industry  
Aerospace Industry  
Defence Industry

### Media Centre

Videos  
Product Catalogue  
2018/2019  
Automotive Catalogue  
2016/2017  
Connectivity Catalogues  
2016/2017  
Brochures  
Software & Drivers  
Helatag & Helafix  
Templates  
Manuals & Operating  
Instructions

Cable clips for edges  
Cable management high  
temperature  
applications

## Events

Update: 07/10/2018

You can easily accept or reject the cookies on this site by choosing one of the following links:

[I accept cookies](#)

[I refuse cookies](#)

[Privacy](#)

[Contact](#) [Terms of Service](#) [Imprint](#) [Privacy Policy](#)

[statement](#)