



power contactor, AC-3e/AC-3, 32 A, 15 kW / 400 V, 3-pole, 110 V AC, 50 Hz / 120 V, 60 Hz, auxiliary contacts: 1 NO + 1 NC, screw terminal, size: S0

|                                                                                                              |                            |
|--------------------------------------------------------------------------------------------------------------|----------------------------|
| product brand name                                                                                           | SIRIUS                     |
| product designation                                                                                          | Power contactor            |
| product type designation                                                                                     | 3RT2                       |
| <b>General technical data</b>                                                                                |                            |
| size of contactor                                                                                            | S0                         |
| product extension                                                                                            |                            |
| • function module for communication                                                                          | No                         |
| • auxiliary switch                                                                                           | Yes                        |
| power loss [W] for rated value of the current                                                                |                            |
| • at AC in hot operating state                                                                               | 6.3 W                      |
| • at AC in hot operating state per pole                                                                      | 2.3 W                      |
| • without load current share typical                                                                         | 2.7 W                      |
| type of calculation of power loss depending on pole                                                          | quadratic                  |
| insulation voltage                                                                                           |                            |
| • of main circuit with degree of pollution 3 rated value                                                     | 690 V                      |
| • of auxiliary circuit with degree of pollution 3 rated value                                                | 690 V                      |
| surge voltage resistance                                                                                     |                            |
| • of main circuit rated value                                                                                | 6 kV                       |
| • of auxiliary circuit rated value                                                                           | 6 kV                       |
| maximum permissible voltage for protective separation between coil and main contacts according to EN 60947-1 | 400 V                      |
| shock resistance at rectangular impulse                                                                      |                            |
| • at AC                                                                                                      | 8,3g / 5 ms, 5,3g / 10 ms  |
| shock resistance with sine pulse                                                                             |                            |
| • at AC                                                                                                      | 13,5g / 5 ms, 8,3g / 10 ms |
| mechanical service life (operating cycles)                                                                   |                            |
| • of contactor typical                                                                                       | 10 000 000                 |
| • of the contactor with added electronically optimized auxiliary switch block typical                        | 5 000 000                  |
| • of the contactor with added auxiliary switch block typical                                                 | 10 000 000                 |
| reference code according to IEC 81346-2                                                                      | Q                          |
| Substance Prohibitance (Date)                                                                                | 10/01/2009                 |
| <b>Ambient conditions</b>                                                                                    |                            |
| installation altitude at height above sea level maximum                                                      | 2 000 m                    |
| ambient temperature                                                                                          |                            |
| • during operation                                                                                           | -25 ... +60 °C             |
| • during storage                                                                                             | -55 ... +80 °C             |
| relative humidity minimum                                                                                    | 10 %                       |
| relative humidity at 55 °C according to IEC 60068-2-30 maximum                                               | 95 %                       |
| <b>Environmental footprint</b>                                                                               |                            |

|                                                                        |                    |
|------------------------------------------------------------------------|--------------------|
| Environmental Product Declaration(EPD)                                 | Yes                |
| Global Warming Potential [CO2 eq] total                                | 74.2 kg            |
| Global Warming Potential [CO2 eq] during manufacturing                 | 1.9 kg             |
| Global Warming Potential [CO2 eq] during operation                     | 72.4 kg            |
| Global Warming Potential [CO2 eq] after end of life                    | -0.117 kg          |
| <b>Main circuit</b>                                                    |                    |
| <b>number of poles for main current circuit</b>                        | 3                  |
| <b>number of NO contacts for main contacts</b>                         | 3                  |
| <b>operating voltage</b>                                               |                    |
| • at AC-3 rated value maximum                                          | 690 V              |
| • at AC-3e rated value maximum                                         | 690 V              |
| <b>operational current</b>                                             |                    |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value            | 50 A               |
| • at AC-1                                                              |                    |
| — up to 690 V at ambient temperature 40 °C rated value                 | 50 A               |
| — up to 690 V at ambient temperature 60 °C rated value                 | 42 A               |
| • at AC-3                                                              |                    |
| — at 400 V rated value                                                 | 32 A               |
| — at 500 V rated value                                                 | 32 A               |
| — at 690 V rated value                                                 | 21 A               |
| • at AC-3e                                                             |                    |
| — at 400 V rated value                                                 | 32 A               |
| — at 500 V rated value                                                 | 32 A               |
| — at 690 V rated value                                                 | 21 A               |
| • at AC-4 at 400 V rated value                                         | 22 A               |
| • at AC-5a up to 690 V rated value                                     | 44 A               |
| • at AC-5b up to 400 V rated value                                     | 26.5 A             |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=20 rated value                  | 30.8 A             |
| — up to 400 V for current peak value n=20 rated value                  | 30.8 A             |
| — up to 500 V for current peak value n=20 rated value                  | 27 A               |
| — up to 690 V for current peak value n=20 rated value                  | 21 A               |
| • at AC-6a                                                             |                    |
| — up to 230 V for current peak value n=30 rated value                  | 20.5 A             |
| — up to 400 V for current peak value n=30 rated value                  | 20.5 A             |
| — up to 500 V for current peak value n=30 rated value                  | 18 A               |
| — up to 690 V for current peak value n=30 rated value                  | 18 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value      | 10 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b> |                    |
| • at 400 V rated value                                                 | 12 A               |
| • at 690 V rated value                                                 | 12 A               |
| <b>operational current</b>                                             |                    |
| • <b>at 1 current path at DC-1</b>                                     |                    |
| — at 24 V rated value                                                  | 35 A               |
| — at 60 V rated value                                                  | 20 A               |
| — at 110 V rated value                                                 | 4.5 A              |
| — at 220 V rated value                                                 | 1 A                |
| — at 440 V rated value                                                 | 0.4 A              |
| — at 600 V rated value                                                 | 0.25 A             |
| • <b>with 2 current paths in series at DC-1</b>                        |                    |
| — at 24 V rated value                                                  | 35 A               |
| — at 60 V rated value                                                  | 35 A               |
| — at 110 V rated value                                                 | 35 A               |
| — at 220 V rated value                                                 | 5 A                |
| — at 440 V rated value                                                 | 1 A                |
| — at 600 V rated value                                                 | 0.8 A              |
| • <b>with 3 current paths in series at DC-1</b>                        |                    |

|                                                                         |                                                           |
|-------------------------------------------------------------------------|-----------------------------------------------------------|
| — at 24 V rated value                                                   | 35 A                                                      |
| — at 60 V rated value                                                   | 35 A                                                      |
| — at 110 V rated value                                                  | 35 A                                                      |
| — at 220 V rated value                                                  | 35 A                                                      |
| — at 440 V rated value                                                  | 2.9 A                                                     |
| — at 600 V rated value                                                  | 1.4 A                                                     |
| ● <b>at 1 current path at DC-3 at DC-5</b>                              |                                                           |
| — at 24 V rated value                                                   | 20 A                                                      |
| — at 60 V rated value                                                   | 5 A                                                       |
| — at 220 V rated value                                                  | 1 A                                                       |
| — at 440 V rated value                                                  | 0.09 A                                                    |
| — at 600 V rated value                                                  | 0.06 A                                                    |
| ● <b>with 2 current paths in series at DC-3 at DC-5</b>                 |                                                           |
| — at 24 V rated value                                                   | 35 A                                                      |
| — at 60 V rated value                                                   | 35 A                                                      |
| — at 110 V rated value                                                  | 15 A                                                      |
| — at 220 V rated value                                                  | 3 A                                                       |
| — at 440 V rated value                                                  | 0.27 A                                                    |
| — at 600 V rated value                                                  | 0.16 A                                                    |
| ● <b>with 3 current paths in series at DC-3 at DC-5</b>                 |                                                           |
| — at 24 V rated value                                                   | 35 A                                                      |
| — at 60 V rated value                                                   | 35 A                                                      |
| — at 110 V rated value                                                  | 35 A                                                      |
| — at 220 V rated value                                                  | 10 A                                                      |
| — at 440 V rated value                                                  | 0.6 A                                                     |
| — at 600 V rated value                                                  | 0.6 A                                                     |
| <b>operating power</b>                                                  |                                                           |
| ● <b>at AC-3</b>                                                        |                                                           |
| — at 230 V rated value                                                  | 7.5 kW                                                    |
| — at 400 V rated value                                                  | 15 kW                                                     |
| — at 500 V rated value                                                  | 15 kW                                                     |
| — at 690 V rated value                                                  | 18.5 kW                                                   |
| ● <b>at AC-3e</b>                                                       |                                                           |
| — at 230 V rated value                                                  | 7.5 kW                                                    |
| — at 400 V rated value                                                  | 15 kW                                                     |
| — at 500 V rated value                                                  | 15 kW                                                     |
| — at 690 V rated value                                                  | 18.5 kW                                                   |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>      |                                                           |
| ● at 400 V rated value                                                  | 6 kW                                                      |
| ● at 690 V rated value                                                  | 10.3 kW                                                   |
| <b>operating apparent power at AC-6a</b>                                |                                                           |
| ● up to 230 V for current peak value n=20 rated value                   | 12.2 kVA                                                  |
| ● up to 400 V for current peak value n=20 rated value                   | 21.3 kVA                                                  |
| ● up to 500 V for current peak value n=20 rated value                   | 23.3 kVA                                                  |
| ● up to 690 V for current peak value n=20 rated value                   | 25 kVA                                                    |
| <b>operating apparent power at AC-6a</b>                                |                                                           |
| ● up to 230 V for current peak value n=30 rated value                   | 8.1 kVA                                                   |
| ● up to 400 V for current peak value n=30 rated value                   | 14.2 kVA                                                  |
| ● up to 500 V for current peak value n=30 rated value                   | 15.5 kVA                                                  |
| ● up to 690 V for current peak value n=30 rated value                   | 21.5 kVA                                                  |
| <b>short-time withstand current in cold operating state up to 40 °C</b> |                                                           |
| ● limited to 1 s switching at zero current maximum                      | 499 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 5 s switching at zero current maximum                      | 341 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 10 s switching at zero current maximum                     | 260 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 30 s switching at zero current maximum                     | 199 A; Use minimum cross-section acc. to AC-1 rated value |
| ● limited to 60 s switching at zero current maximum                     | 162 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b>                                      |                                                           |
| ● at AC                                                                 | 5 000 1/h                                                 |
| <b>operating frequency</b>                                              |                                                           |

|                                                                                                                                                                                                                                                                       |                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at AC-1 maximum</li> <li>• at AC-2 maximum</li> <li>• at AC-3 maximum</li> <li>• at AC-3e maximum</li> <li>• at AC-4 maximum</li> </ul>                                                                                      | 1 000 1/h<br>750 1/h<br>750 1/h<br>750 1/h<br>250 1/h |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                       |                                                       |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                  | AC                                                    |
| <b>control supply voltage at AC</b>                                                                                                                                                                                                                                   |                                                       |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul>                                                                                                                                                              | 110 V<br>120 V                                        |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b>                                                                                                                                                                                 |                                                       |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                      | 0.8 ... 1.1<br>0.8 ... 1.1                            |
| <b>apparent pick-up power of magnet coil at AC</b>                                                                                                                                                                                                                    |                                                       |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                      | 81 VA<br>79 VA                                        |
| <b>inductive power factor with closing power of the coil</b>                                                                                                                                                                                                          |                                                       |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                      | 0.72<br>0.74                                          |
| <b>apparent holding power of magnet coil at AC</b>                                                                                                                                                                                                                    |                                                       |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                      | 10.5 VA<br>8.5 VA                                     |
| <b>inductive power factor with the holding power of the coil</b>                                                                                                                                                                                                      |                                                       |
| <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                      | 0.25<br>0.28                                          |
| <b>closing delay</b>                                                                                                                                                                                                                                                  |                                                       |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                             | 8 ... 40 ms                                           |
| <b>opening delay</b>                                                                                                                                                                                                                                                  |                                                       |
| <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                             | 4 ... 16 ms                                           |
| <b>arcing time</b>                                                                                                                                                                                                                                                    | 10 ... 10 ms                                          |
| <b>control version of the switch operating mechanism</b>                                                                                                                                                                                                              | Standard A1 - A2                                      |
| <b>Auxiliary circuit</b>                                                                                                                                                                                                                                              |                                                       |
| number of NC contacts for auxiliary contacts instantaneous contact                                                                                                                                                                                                    | 1                                                     |
| number of NO contacts for auxiliary contacts instantaneous contact                                                                                                                                                                                                    | 1                                                     |
| operational current at AC-12 maximum                                                                                                                                                                                                                                  | 10 A                                                  |
| <b>operational current at AC-15</b>                                                                                                                                                                                                                                   |                                                       |
| <ul style="list-style-type: none"> <li>• at 230 V rated value</li> <li>• at 400 V rated value</li> <li>• at 500 V rated value</li> <li>• at 690 V rated value</li> </ul>                                                                                              | 10 A<br>3 A<br>2 A<br>1 A                             |
| <b>operational current at DC-12</b>                                                                                                                                                                                                                                   |                                                       |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> <li>• at 48 V rated value</li> <li>• at 60 V rated value</li> <li>• at 110 V rated value</li> <li>• at 125 V rated value</li> <li>• at 220 V rated value</li> <li>• at 600 V rated value</li> </ul> | 10 A<br>6 A<br>6 A<br>3 A<br>2 A<br>1 A<br>0.15 A     |
| <b>operational current at DC-13</b>                                                                                                                                                                                                                                   |                                                       |
| <ul style="list-style-type: none"> <li>• at 24 V rated value</li> <li>• at 48 V rated value</li> <li>• at 60 V rated value</li> <li>• at 110 V rated value</li> <li>• at 125 V rated value</li> <li>• at 220 V rated value</li> <li>• at 600 V rated value</li> </ul> | 10 A<br>2 A<br>2 A<br>1 A<br>0.9 A<br>0.3 A<br>0.1 A  |
| <b>contact reliability of auxiliary contacts</b>                                                                                                                                                                                                                      | 1 faulty switching per 100 million (17 V, 1 mA)       |
| <b>UL/CSA ratings</b>                                                                                                                                                                                                                                                 |                                                       |

|                                                                   |                                                                                                                                      |
|-------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| <b>full-load current (FLA) for 3-phase AC motor</b>               |                                                                                                                                      |
| • at 480 V rated value                                            | 27 A                                                                                                                                 |
| • at 600 V rated value                                            | 27 A                                                                                                                                 |
| <b>yielded mechanical performance [hp]</b>                        |                                                                                                                                      |
| • for single-phase AC motor                                       |                                                                                                                                      |
| — at 110/120 V rated value                                        | 2 hp                                                                                                                                 |
| — at 230 V rated value                                            | 5 hp                                                                                                                                 |
| • for 3-phase AC motor                                            |                                                                                                                                      |
| — at 200/208 V rated value                                        | 10 hp                                                                                                                                |
| — at 220/230 V rated value                                        | 10 hp                                                                                                                                |
| — at 460/480 V rated value                                        | 20 hp                                                                                                                                |
| — at 575/600 V rated value                                        | 25 hp                                                                                                                                |
| <b>contact rating of auxiliary contacts according to UL</b>       | A600 / P600                                                                                                                          |
| <b>Short-circuit protection</b>                                   |                                                                                                                                      |
| <b>design of the fuse link</b>                                    |                                                                                                                                      |
| • for short-circuit protection of the main circuit                |                                                                                                                                      |
| — with type of coordination 1 required                            | gG: 125A (690V,100kA), aM: 50A (690V,100kA), BS88: 125A (415V,80kA)                                                                  |
| — with type of assignment 2 required                              | gG: 50A (690V,100kA), aM: 25A (690V, 100kA), BS88: 50A (415V, 80kA)                                                                  |
| • for short-circuit protection of the auxiliary switch required   | gG: 10 A (500 V, 1 kA)                                                                                                               |
| <b>Installation/ mounting/ dimensions</b>                         |                                                                                                                                      |
| <b>mounting position</b>                                          | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| <b>fastening method</b>                                           | screw and snap-on mounting onto 35 mm DIN rail according to DIN EN 60715                                                             |
| <b>height</b>                                                     | 85 mm                                                                                                                                |
| <b>width</b>                                                      | 45 mm                                                                                                                                |
| <b>depth</b>                                                      | 97 mm                                                                                                                                |
| <b>required spacing</b>                                           |                                                                                                                                      |
| • with side-by-side mounting                                      |                                                                                                                                      |
| — forwards                                                        | 10 mm                                                                                                                                |
| — upwards                                                         | 10 mm                                                                                                                                |
| — downwards                                                       | 10 mm                                                                                                                                |
| — at the side                                                     | 0 mm                                                                                                                                 |
| • for grounded parts                                              |                                                                                                                                      |
| — forwards                                                        | 10 mm                                                                                                                                |
| — upwards                                                         | 10 mm                                                                                                                                |
| — at the side                                                     | 6 mm                                                                                                                                 |
| — downwards                                                       | 10 mm                                                                                                                                |
| • for live parts                                                  |                                                                                                                                      |
| — forwards                                                        | 10 mm                                                                                                                                |
| — upwards                                                         | 10 mm                                                                                                                                |
| — downwards                                                       | 10 mm                                                                                                                                |
| — at the side                                                     | 6 mm                                                                                                                                 |
| <b>Connections/ Terminals</b>                                     |                                                                                                                                      |
| <b>type of electrical connection</b>                              |                                                                                                                                      |
| • for main current circuit                                        | screw-type terminals                                                                                                                 |
| • for auxiliary and control circuit                               | screw-type terminals                                                                                                                 |
| • at contactor for auxiliary contacts                             | Screw-type terminals                                                                                                                 |
| • of magnet coil                                                  | Screw-type terminals                                                                                                                 |
| <b>type of connectable conductor cross-sections</b>               |                                                                                                                                      |
| • for main contacts                                               |                                                                                                                                      |
| — solid                                                           | 2x (1 ... 2.5 mm²), 2x (2.5 ... 10 mm²)                                                                                              |
| — solid or stranded                                               | 2x (1 ... 2.5 mm²), 2x (2.5 ... 10 mm²)                                                                                              |
| — finely stranded with core end processing                        | 2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²), 1x 10 mm²                                                                                    |
| • for AWG cables for main contacts                                | 2x (16 ... 12), 2x (14 ... 8)                                                                                                        |
| <b>connectable conductor cross-section for main contacts</b>      |                                                                                                                                      |
| • solid                                                           | 1 ... 10 mm²                                                                                                                         |
| • stranded                                                        | 1 ... 10 mm²                                                                                                                         |
| • finely stranded with core end processing                        | 1 ... 10 mm²                                                                                                                         |
| <b>connectable conductor cross-section for auxiliary contacts</b> |                                                                                                                                      |
| • solid or stranded                                               | 0.5 ... 2.5 mm²                                                                                                                      |
| • finely stranded with core end processing                        | 0.5 ... 2.5 mm²                                                                                                                      |

|                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>type of connectable conductor cross-sections</b> <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> </ul> </li> <li>• for AWG cables for auxiliary contacts</li> </ul> | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 16), 2x (18 ... 14) |
| <b>AWG number as coded connectable conductor cross section</b> <ul style="list-style-type: none"> <li>• for main contacts</li> <li>• for auxiliary contacts</li> </ul>                                                                                                                                     | 16 ... 8<br>20 ... 14                                                                                                                                                            |

|                                                                                                                                                                                                                                 |                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| <b>Safety related data</b>                                                                                                                                                                                                      |                                                  |
| <b>product function</b> <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> <li>• positively driven operation according to IEC 60947-5-1</li> <li>• suitable for safety function</li> </ul> | Yes<br>No<br>Yes                                 |
| suitability for use safety-related switching OFF                                                                                                                                                                                | Yes                                              |
| <b>service life maximum</b>                                                                                                                                                                                                     | 20 a                                             |
| <b>test wear-related service life necessary</b>                                                                                                                                                                                 | Yes                                              |
| <b>proportion of dangerous failures</b> <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul>                                   | 40 %<br>73 %                                     |
| <b>B10 value with high demand rate according to SN 31920</b>                                                                                                                                                                    | 1 000 000                                        |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b>                                                                                                                                                            | 100 FIT                                          |
| <b>ISO 13849</b>                                                                                                                                                                                                                |                                                  |
| <b>device type according to ISO 13849-1</b>                                                                                                                                                                                     | 3                                                |
| <b>overdimensioning according to ISO 13849-2 necessary</b>                                                                                                                                                                      | Yes                                              |
| <b>IEC 61508</b>                                                                                                                                                                                                                |                                                  |
| <b>safety device type according to IEC 61508-2</b>                                                                                                                                                                              | Type A                                           |
| <b>T1 value</b> <ul style="list-style-type: none"> <li>• for proof test interval or service life according to IEC 61508</li> </ul>                                                                                              | 20 a                                             |
| <b>Electrical Safety</b>                                                                                                                                                                                                        |                                                  |
| <b>protection class IP on the front according to IEC 60529</b>                                                                                                                                                                  | IP20                                             |
| <b>touch protection on the front according to IEC 60529</b>                                                                                                                                                                     | finger-safe, for vertical contact from the front |
| <b>Approvals Certificates</b>                                                                                                                                                                                                   |                                                  |
| <b>General Product Approval</b>                                                                                                                                                                                                 |                                                  |



[Confirmation](#)



[KC](#)

|                          |     |                   |                   |                   |
|--------------------------|-----|-------------------|-------------------|-------------------|
| General Product Approval | EMV | Functional Safety | Test Certificates | Marine / Shipping |
|--------------------------|-----|-------------------|-------------------|-------------------|



[Type Examination Certificate](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



|                   |       |
|-------------------|-------|
| Marine / Shipping | other |
|-------------------|-------|



[Miscellaneous](#)

[Confirmation](#)

|       |         |             |
|-------|---------|-------------|
| other | Railway | Environment |
|-------|---------|-------------|



## Further information

## Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

## Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

## Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2027-1AK60>

## Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2027-1AK60>

## Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2027-1AK60>

## Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)




[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2027-1AK60&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2027-1AK60&lang=en)

Characteristic: Tripping characteristics,  $I^2t$ , Let-through current


<https://support.industry.siemens.com/cs/ww/en/ps/3RT2027-1AK60/char>

## Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2027-1AK60&objecttype=14&gridview=view1>







**last modified:**

7/19/2024 