

# Printed-circuit board connector - MSTBV 2,5/8-GF BK P26 - 1703383

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)


PCB headers, nominal current: 12 A, number of positions: 8, pitch: 5 mm, color: black, contact surface: Tin, mounting: Wave soldering



The figure shows a 10-position version of the product

### Your advantages

- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- Well-known mounting principle allows worldwide use
- ✓ Vertical connection enables multi-row arrangement on the PCB





### **Key Commercial Data**

Packing unit	50 pc
GTIN	4 046356 650083
GTIN	4046356650083

### Technical data

#### **Dimensions**

Pitch	5 mm
Dimension a	35 mm
Height	12 mm
Length of the solder pin	2.6 mm
Pin dimensions	1 x 1 mm

#### General

Range of articles	MSTBV 2,5/GF
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	12 A
Color	black



# Printed-circuit board connector - MSTBV 2,5/8-GF BK P26 - 1703383

## Technical data

General	
Number of positions	8
Standards and Regulations	
Connection in acc. with standard	EN-VDE
Environmental Product Compliance	
REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC EHL	B.01742

Phoenix Contact 2018 @ - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8

32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1703383