




Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**

Connector System: **Wire-to-Board**

Number of Positions: **4**

Number of Rows: **2**

Centerline (Pitch): **3 mm [.118 in]**

Features

Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Mixed & Hybrid Header             | No                    |
| Connector Shape                   | Rectangular           |
| PCB Connector Assembly Type       | PCB Mount Header      |
| Connector System                  | Wire-to-Board         |
| Header Type                       | Fully Shrouded        |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

|                                  |              |
|----------------------------------|--------------|
| Number of Power Positions        | 4            |
| Number of Columns                | 2            |
| Number of Loaded Positions       | 4            |
| Connector Contact Load Condition | Fully Loaded |
| Number of Positions              | 4            |
| Number of Rows                   | 2            |



|                       |             |
|-----------------------|-------------|
| PCB Mount Orientation | Right Angle |
|-----------------------|-------------|

Electrical Characteristics

|                   |         |
|-------------------|---------|
| Operating Voltage | 250 VAC |
|-------------------|---------|

Body Features

|                                        |                 |
|----------------------------------------|-----------------|
| PCB Retention Feature Material         | Phosphor Bronze |
| PCB Retention Feature Plating Material | Tin             |
| Primary Product Color                  | Black           |

Contact Features

|                                                         |                               |
|---------------------------------------------------------|-------------------------------|
| Contact Mating Area Length                              | 4.15 mm[.163 in]              |
| Contact Size                                            | .64mm                         |
| Mating Square Post Dimension                            | .64 mm[.025 in]               |
| PCB Contact Termination Area Plating Material Thickness | 2.54 – 7.62 µm[100 – 300 µin] |
| Contact Layout                                          | Matrix                        |
| Contact Underplating Material Thickness                 | 1.27 – 2.54 µm[50 – 100 µin]  |
| Contact Mating Area Plating Material Thickness          | 2.54 – 7.62 µm[100 – 300 µin] |
| PCB Contact Termination Area Plating Material Finish    | Matte                         |
| Contact Shape & Form                                    | Square                        |
| Contact Mating Area Plating Material Finish             | Matte                         |
| Contact Underplating Material                           | Nickel                        |
| PCB Contact Termination Area Plating Material           | Tin                           |
| Contact Base Material                                   | Brass                         |
| Contact Mating Area Plating Material                    | Tin                           |
| Contact Type                                            | Tab                           |
| Contact Current Rating (Max)                            | 5 A                           |

Termination Features

|                                          |                 |
|------------------------------------------|-----------------|
| Square Termination Post & Tail Dimension | .64 mm[.025 in] |
| Termination Method to PCB                | Surface Mount   |

Mechanical Attachment

|                          |              |
|--------------------------|--------------|
| Mating Alignment Type    | Polarization |
| Mating Retention         | With         |
| Panel Mount Feature      | Without      |
| PCB Mount Retention Type | Hold-Down    |
|                          |              |



|                         |             |
|-------------------------|-------------|
| Mating Retention Type   | Locking Tab |
| Connector Mounting Type | Board Mount |
| Mating Alignment        | With        |
| PCB Mount Alignment     | Without     |
| PCB Mount Retention     | With        |

Housing Features

|                       |                        |
|-----------------------|------------------------|
| Mating Entry Location | Side                   |
| Housing Material      | High Temperature Nylon |
| Centerline (Pitch)    | 3 mm [.118 in]         |

Dimensions

|                             |                   |
|-----------------------------|-------------------|
| Connector Length            | 10 mm [.394 in]   |
| Connector Height            | 7.37 mm [.29 in]  |
| PCB Thickness (Recommended) | 1.57 mm [.062 in] |
| Row-to-Row Spacing          | 3 mm [.118 in]    |

Usage Conditions

|                             |                             |
|-----------------------------|-----------------------------|
| Operating Temperature (Max) | 105 °C [221 °F]             |
| Operating Temperature Range | -40 – 105 °C [-40 – 221 °F] |

Operation/Application

|                     |       |
|---------------------|-------|
| Circuit Application | Power |
|---------------------|-------|

Industry Standards

|                                             |                           |
|---------------------------------------------|---------------------------|
| UL Rating                                   | Recognized                |
| Glow Wire Rating                            | GWT 750°C (Without Flame) |
| Compatible With Agency/Standards Products   | CNR, USR, VDE             |
| Compatible With Approved Standards Products | UL E28476, VDE 40005280   |
| UL Flammability Rating                      | UL 94V-0                  |

Packaging Features

|                    |      |
|--------------------|------|
| Packaging Quantity | 150  |
| Packaging Method   | Tape |

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|                              |           |
|------------------------------|-----------|
| EU RoHS Directive 2011/65/EU | Compliant |
|------------------------------|-----------|






|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                             |
| Solder Process Capability                     | Reflow solder capable to 260°C                                                                                                  |

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 794617-4  
4POS,MICRO MNL,RCPT HSG

Also in the Series | Micro MATE-N-LOK

|                                                                                     |                                                                                     |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |
| Connector Contacts(27)                                                              | Insertion & Extraction Tools(1)                                                     | PCB Headers & Receptacles(371)                                                        | Rectangular Power Connectors(98)                                                      |



Customers Also Bought



TE Part #5499160-6  
A/L UNIV HDR 26P VERT SHT LAT



TE Part #4-794627-6  
16P MICRO MNL ASSY,RA,SMT,LF



TE Part #1-770621-0  
12P MINI UMNL DBL ROW HDR ASSY



TE Part #1-770872-0  
02P MINI UMNL HDR ASSY SN



TE Part #2-1445050-2  
MICRO MNL HDR ASSY S/ROW LF



TE Part #1-770875-0  
06P MINI UMNL HDR ASSY SN



TE Part #2-1445050-3  
MICRO MNL HDR ASSY S/ROW LF



TE Part #2-1445091-2  
MICRO MNL HDR ASSY S/ROW AU LF



TE Part #350713-1  
12P UMNL PIN HDR ASSY 94VO



TE Part #3-1734035-2  
Mini USB,R/A,SMT,matte tin,w/o mylar

Documents

Product Drawings

04P MICRO MNL ASSY,RA ,SMT, LF

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_3-794627-4\_K.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_3-794627-4\_K.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_3-794627-4\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.



Datasheets & Catalog Pages

SOFT\_SHELL\_PIN\_AND\_SOCKET\_CONNECTORS\_CATALOG

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

Product Specifications

Application Specification

English

Agency Approvals

VDE Certificate

English