



Manufacturer of High Quality Relays &amp; Controls

**Catalog Search**By Keyword 

GO

**Relay Products****Inventory Locator**

General Purpose

Traffic Cabinet Relays

Power Contactors

Motor Reversing

Latching/Sequencing

Special Purpose &amp; Custom Design

Sensitive - Low Input Power

Timer/Sensor

Reed

Accessories and Sockets

[Home](#)[Product Catalog](#)[Literature](#)[Sales Channels](#)[Industries Served](#)[About Us](#)[News](#)[RFQ/RFI](#)[Careers](#)[Contact](#)**Search Catalog**By Keyword 


Go

☒ All Categories ☐ PM Series - Open Style Power Relays[All Categories](#) > [Power Relays & Contactors](#) > [PM Series - Open Style Power Relays](#) > Item # PM-17DY-24VDC[Download PDF](#)[Printable Page](#)[Email This Page](#)[Save To Favorites](#)**Request Information****Item # PM-17DY-24VDC, PM Series - Open Style Power Relays**

The PM Series relays offer 4 double throw poles (4PDT) for up to 35 amp at 240 VAC or 20 amps at 28VDC. Product also is capable of 10 amps tungsten switching. Screw terminals (#M4) are standard but .250" quick connects are also available.

This is the same Potter & Brumfield relay that we acquired from them in 2003! It is made to the same original specifications. You can check which of our Distributors have inventory for the relay you need by clicking the Inventory Locator near the top of the left column and enter the part number you need. Contact us if you have any questions.

**Additional contact configurations and coil options are available – please use the RFQ/RFI tab above to submit your request.**

[larger image](#)[larger image](#)**MORE IMAGES**

- PM Series - Open Style Power Relays - Wiring Diagram

**VIEW CAD DRAWING**

- 3D
- 2D Front View
- 2D Left Side View
- 2D Bottom View
- 2D Sales Drawing

**DOWNLOADS**

- PM Series - Open Style Power Relays - Product Brochure (PDF, 303KB)

**Optional Dust Cover**[PM Dust Cover](#)
[Specifications](#) · [Contacts](#) · [Coil](#) · [Timing](#) · [Dielectric Strength](#) · [Temperature](#) · [Life Expectancy](#) · [Miscellaneous](#)
**Specifications**

<b>Series</b>	PM
<b>Type</b>	Screw Terminals (#M4 - 7.0 x 5mm)
<b>Contact Arrangement</b>	4 form C (4PDT)
<b>Coil Voltage</b>	24 VDC

**Contacts**

<b>Contact Configuration</b>	4PDT
<b>Contact Material</b>	Silver Alloy
<b>Contact Rating</b>	35 A
<b>Contact Rating 120 / 240VAC Resistive</b>	35 A
<b>Contact Rating 28VDC Resistive</b>	20 A
<b>Motor 240VAC 1 Phase</b>	1.5 hp
<b>Contact Resistance, Initial</b>	100 milliohms max at 6VDC

**Coil**

<b>Coils Available</b>	AC and DC
<b>Nominal Coil Power AC</b>	14 VA
<b>Nominal Coil Power DC</b>	4.4 W
<b>Input Voltage Tolerance - AC</b>	85% to 110% of nominal
<b>Input Voltage Tolerance - DC</b>	80% to 110% of nominal
<b>Drop-out voltage</b>	10% of nominal
<b>Duty</b>	Continuous

#### Timing

<b>Operate Time (max)</b>	40 ms
<b>Release Time (max)</b>	30 ms

#### Dielectric Strength

<b>Across Open Contacts</b>	1500 Vrms
<b>Between Mutually Insulated Point</b>	2000 Vrms
<b>Insulation Resistance</b>	1000 megohms at 500VAC

#### Temperature

<b>Operating</b>	-34 to 74 °C -30 to 165 °F
<b>Storage</b>	-40 to 105 °C -40 to 221 °F

#### Life Expectancy

<b>Electrical (full load)</b>	100,000
<b>Mechanical (no load)</b>	2,000,000

#### Miscellaneous

<b>Mounting Position</b>	Any
<b>Enclosure</b>	Optional - 35D203
<b>Weight</b>	14.9 oz 379 g

#### Request Information

**Struthers-Dunn** | 407 East Smith Street - Suite B, Timmonsville, SC 29161

Tel (843) 346-4427 | Fax (843) 346-4465 | E-Mail: [info@struthers-dunn.com](mailto:info@struthers-dunn.com) | [www.struthers-dunn.com](http://www.struthers-dunn.com) | [Sitemap](#) | [Privacy Policy](#)