

M12 Connector

TE Internal #: T4112012051-000

Cable-to-Cable, 5 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard

Circular Connectors

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors











Connector System: Cable-to-Cable

Connector Mounting Type: Cable Mount (Free-Hanging)

Number of Positions: 5

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Features

Product Type Features

| Troduct Type reduces | |
|---------------------------------------|----------------------|
| Product Type | Connector Assembly |
| Accessory Color | Black |
| Assembly Requirement | Factory Assembled |
| Assembly Type | Electrical Connector |
| Circular Connector Shell Type | Metal-Shell |
| Connector Product Type | Connector Assembly |
| Connector System | Cable-to-Cable |
| Sealable | Yes |
| Connector & Contact Terminates To | Wire & Cable |
| Circular Connector Type | Receptacle |
| Shell Type | Metal |
| Configuration Features | |
| Keying & Polarized Position Locations | A |
| | |

With

Factory Installed Backshell



| Keying | A |
|--|---|
| Number of Positions | 5 |
| Number of Power Positions | 0 |
| Number of Signal Positions | 5 |
| Contacts Preloaded | Yes |
| Electrical Characteristics | |
| Operating Voltage | 60 VAC |
| Voltage | 250 Vrms |
| Body Features | |
| Peripheral Seal Material | Silicone |
| Environmental Protection | IP67 |
| O-Ring Material | Silicone |
| Environmental Protection Type | Elastomer Sealed |
| Shell Plating Material | Nickel |
| Shell Base Material | Copper Alloy |
| Circular Connector Insulation Material Type | Polyamide 66 GF25 |
| | |
| Hermetically Sealed | Yes |
| | Yes |
| Hermetically Sealed | Yes 4 A |
| Hermetically Sealed Contact Features | |
| Hermetically Sealed Contact Features Contact Current Rating (Max) | 4 A |
| Hermetically Sealed Contact Features Contact Current Rating (Max) Reverse Gender | 4 A Yes |
| Hermetically Sealed Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type | 4 A Yes |
| Hermetically Sealed Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment | 4 A Yes Socket |
| Hermetically Sealed Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type | 4 A Yes Socket Threaded Coupling |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type Mating Alignment | 4 A Yes Socket Threaded Coupling With |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type | 4 A Yes Socket Threaded Coupling With Cable Mount (Free-Hanging) |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type Polarization Code | 4 A Yes Socket Threaded Coupling With Cable Mount (Free-Hanging) A |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type Polarization Code Mating Alignment Type | 4 A Yes Socket Threaded Coupling With Cable Mount (Free-Hanging) A |
| Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type Polarization Code Mating Alignment Type Housing Features | 4 A Yes Socket Threaded Coupling With Cable Mount (Free-Hanging) A Keyed |
| Hermetically Sealed Contact Features Contact Current Rating (Max) Reverse Gender Circular Connector Contact Type Mechanical Attachment Mating Retention Type Mating Alignment Connector Mounting Type Polarization Code Mating Alignment Type Housing Features Circular Connector Shell Size | 4 A Yes Socket Threaded Coupling With Cable Mount (Free-Hanging) A Keyed |



| IP Dust Sealing Level | 6 |
|-----------------------------|---------------------------|
| IP Water Sealing Level | IP67 |
| Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
| Operation/Application | |
| Durability Rating | 100 Cycles |
| Circuit Application | Signal |
| Shielded | Yes |
| Industry Standards | |
| UL Flammability Rating | UL 94HB |
| Other | |
| Position Locations Omitted | 0 |
| Field Serviceable | Yes |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|--|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # T4113012051-000 M12 M, 5P GOLD A_CODE RA SHIELDED PG9



TE Part # 225266-E M12 MALE, UNI CODE,RA, 5P THR REAR MOUNT



TE Part # 484118-E M12 MALE, A CODE, 5P, 17MM THR



TE Part # 225242-E M12 MALE, A CODE, RA, 5P THR FRONT MOUNT



TE Part # 225251-E M12 MALE, A CODE, RA, 5P THR REAR MOUNT



TE Part # 225254-E M12 MALE, A CODE, RA, 5P THR REAR MOUNT



TE Part # 225456-E M12 MALE, A CODE, RA, 5P THR REAR MOUNT



TE Part # 235165-E M12 MALE, A CODE, RA, 5P THR REAR MOUNT



TE Part # 244790-E M12 MALE, A CODE, 5P, 17MM SMT



TE Part # 244934-E M12 MALE, A CODE, 5P, 10.5MM SMT



TE Part # 284740-E M12 MALE, A CODE, 5P, 10.5MM SMT



TE Part # 354132-E M12 MALE, A CODE, 5P, 10.5MM SMT



TE Part # 364767-E M12 MALE, A CODE, 5P, 17MM SMT



TE Part # 364779-E M12 MALE, UNI CODE, 5P, 10.5MM THR, DI



TE Part # 374352-E M12 MALE, A CODE, 5P, 17MM THR



TE Part # 384814-E M12 MALE, UNI CODE, 5P, 10.5MM THR, DI

Cable-to-Cable, 5 Position, Sealable, Wire & Cable, Signal, Cable Mount (Free-Hanging), Reverse Gender, M12 Connector, Standard Circular Connectors





TE Part # 394337-E M12 MALE, UNI CODE, 5P, 10.5MM SMT, DI



TE Part # 394339-E M12 MALE, UNI CODE. 4P, 10.5MM SMT, DI



TE Part # 454828-E M12 MALE, A CODE, 5P, 17MM SMT



Also in the Series | M12 Connector



Connector Caps & Covers(5)




Connector Hardware(12)



Connector Seals & Cavity Plugs(4)



M8/M12 Cable Assemblies(230)



Customers Also Bought







SHIELDED PG9







M12 F, 5P GOLDR A_CODE S

SHIELDED PG7









Documents

Product Drawings

M12 F, 5P GOLD A_CODE RA SHIELDED PG9

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_T4112012051-000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_T4112012051-000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4112012051-000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Application Specification

English

Agency Approvals

UL

English