



PennEngineering
Corporate Headquarters – Danboro, PA
 5190 Old Easton Rd.
 Danboro, PA 18916
Phone: 215-766-8853
Toll-Free Phone: 1-800-237-4736 (U.S. only)
Email: info@pemnet.com
Website: www.pemnet.com

Part # KFSE-3.6-8, Broaching Standoffs - Types KFE, KFSE - Metric

No matter how sophisticated or advanced, electronic components must be attached reliably and securely if they are to deliver optimum performance. We offer several fastener products for use with PC boards to satisfy component-to-board, board-to-board, and board-to-chassis attachment needs.

Broaching fasteners can also offer practical alternatives to “loose” hardware. They install permanently in all types of PC boards, as well as aluminum, acrylic, casting and polycarbonate components. A broaching

[+ more](#)



Specifications

Thru Hole + 0.10 -0.08	3.6 mm
L - Length ± 0.13	8 mm
A (Shank) Max.	1.53 mm
Min. Sheet Thickness	1.53 mm
Hole Size in Sheet + 0.08	5.41 mm
C ± 0.08	5.87 mm
E ± 0.13	7.14 mm
Min. Dist. Hole C/L to Edge	5.5 mm
For Use in Sheet Hardness¹	HRB 70 / HB 125 or Less PC Board
Thread Specification	Internal, ASME B1.13M, 6H
Fastener Material	300 Series Stainless Steel



Standard Finish	Passivated and/or tested	per ASTM A380
CAD Supplier	PennEngineering® (PEM®)	

¹ HRB - Hardness Rockwell "B" Scale. HB - Hardness Brinell.