







DCF-C-212E(03.08)




791101RS
('ON 0NIMV8D) ㄣㄣㄣㄣ



SECT. A-A
(SCALE 2:1)




PANEL CUT OUT DIMENSION(REF.)(SCALE 2:1)
筐体間口寸法(参考)(尺度 2:1)



APPLICABLE P.C.B DIMENSION(REF.)(SCALE 2:1)
適合基板寸法(参考)(尺度 2:1)

- NOTE 1. RECOMMENDED SCREW IS JIS B 1122 M3 TAPPING SCREW 2GRADE. 6mm LENGTH.
2. APPLICABLE PRINTED CIRCUIT BOARD:THICKNESS 1.6mm.
3. RECOMMENDED PANEL POSITION IN CONNECT PANEL AND CONNECTOR SHELL AS GROUND.
(DISTANCE BETWEEN P.C.B TO PANEL) : 17.7±0.5mm
4. TERMINAL NUMBER OF THE CONNECTOR IS SHOWN IN RIGHT FIGURE.

- 注1. 推奨取り付ネジ: JIS B 1122 M3×6 タッピンナベネジ 2種.
2. 適用プリント基板: 板厚 1.6mm.
3. 筐体にグラント接続する場合の筐体推奨位置(基板上面から筐体内面までの距離) : 17.7±0.5mm
4. コネクタの端子番号は右図による.



5	SHELL	1	COPPER ALLOY	TIN PLATING	_____
4	GND TERMINAL	1	COPPER ALLOY	TIN PLATING	_____
3	HOUSING B	1	30%GF SPS	_____	COLOR:BLACK
2	HOUSING A	1	30%GF SPS	_____	COLOR:LIGHT BLUE
1	TERMINAL	2	BRASS	SELECTIVE GOLD PLATING SELECTIVE TIN PLATING	_____
符 号 NO.	名 称 DESCRIPTION	個 数 QTY.	材 料 MATERIAL	仕 上 FINISH	備 考 REMARKS

仕様書 (SPECIFICATION)		第1版 (ORIGINAL DATE)		尺度 (SCALE)	シリーズ (SERIES)	日本航空電子工業株式会社 JAPAN AVIATION ELECTRONICS  INDUSTRY, LTD. 図面番号 (DRAWING NO.) SJ101167
		30.Sep.2004		1: 1	MX38	
一般公差 (GENERAL TOLERANCE)		製図 DR.	_____	名称 (TITLE) MX38002UQ1		
		担当 CHK.	H.ITAKURA			
		査閲 APPD.	_____			
		承認 APPD.	T.OKA			
寸法 (DIMENSION)	角度 (ANGLES)			質量 (MASS)		
. ± 0.3	X° ±			_____		
.X ± 0.3	X°X' ±					
.XX ± 0.3						
.XXX ±						

REFERENCE ONLY


特別管理品目
SPECIAL CONTROL ITEM
MX(AUTO)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JAE Electronics:](#)

[MX38002S0008824](#) [MX38002NQ4](#)