

Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

## Surge Protection and Filtering

Surge energy rating	490 Joules
Filtering	Full time multi -pole noise filtering : 0.3% IEEE surge let-through : zero clamp time : meets UL 1449

## Physical

Maximum Height	86.00 mm
Maximum Width	432.00 mm
Maximum depth	678.00 mm
Rack Height	2U
Net Weight	46.82 KG
Shipping Weight	56.82 KG
Shipping Height	250.00 mm
Shipping Width	596.00 mm
Shipping Depth	980.00 mm
Color	Black
Units per Pallet	8.00

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-20 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-9000 meters
Audible noise at 1 meter from surface of unit	55.00 dBA
Online Thermal Dissipation	300.00 BTU/hr

## Conformance

Regulatory Approvals	C-tick,CE,EN 50091 -2,EN 55022 Class A,EN 61000-3-2,GOST
Standard Warranty	2 years repair or replace

\*\*The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the