

Feed-through header - MCV 1,5/6-G-3,5 GY SO - 1700992

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB headers, nominal current: 8 A, number of positions: 6, pitch: 3.5 mm, color: gray, contact surface: Tin, mounting: Wave soldering



The figure shows a 10-position version of the product

Your advantages

- ☑ Well-known mounting principle allows worldwide use
- ✓ Vertical connection enables multi-row arrangement on the PCB
- Maximum flexibility when it comes to device design one header for connectors with different connection technologies









Key Commercial Data

Packing unit	50 pc
GTIN	4 046356 508698
GTIN	4046356508698

Technical data

Dimensions

Pitch	3.5 mm
Dimension a	17.5 mm
Height	10 mm
Length of the solder pin	3.4 mm
Pin dimensions	0.8 x 0.8 mm

General

Range of articles	MCV 1,5/G
Rated voltage (III/3)	160 V
Connection in acc. with standard	EN-VDE
Nominal current I _N	8 A
Color	gray



Feed-through header - MCV 1,5/ 6-G-3,5 GY SO - 1700992

Technical data

General		
Number of positions	6	
Standards and Regulations		
Connection in acc. with standard	EN-VDE	
Environmental Product Compliance		
China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	
Approvals		
Approvals		
Approvals		
EAC		
Ex Approvals		
Approval details		
EAC EN	B.01742	

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1700992