RT5FC-B - REAN Connectors 6/11/2014



Home

Products

Contact

Downloads



Q

Products > TINY xlr > TINY xlr Cable Connectors > RT5FC-B

print

RT5FC-B

5 pole TINY xIr female cable connector, black metal shell, gold plated contacts, bulk packaging available (*-D)

- Easy to assemble
- · Robust metal housing with best flex relief
- Shielded system high noise immunity and EMI protection
- Intuitive and rugged locking mechanism provides secure locking system
- Millionfond proven chuck type strain relief up to 4.00 mm cable diameter
- Keyed insert and strain relief to avoid mispositioning / rotation of insert respectively cable



Downloads









Technical	Information	•	hide	

Product		
Title	RT5FC-B	
E		
Electrical		
Contact resistance	$<$ 10 m Ω (inner)	
Dielectric strength	> 0.5 kVdc	
Insulation resistance	> 1 GΩ	
Rated current per contact	< 5 A	
Mechanical		
Mechanical		
Cable O.D.	2.0 - 4.0 mm	
Lifetime	> 5000 mating cycles	
Wiresize	0.22 mm ²	
Wiresize	24 AWG	
Material		
Boot	EPDM, ZnAl4Cu1, diecast rubber boot	
Contacts	Bronze (CuSn6)	
Shell	Zinc diecast (ZnAl4Cu1)	
Strain relief	PVC	
Environmental		
Temperature range	-30 °C to +85 °C	

© Neutrik® AG | All rights reserved Sitemap | Legal Notices

RT5FC-B - REAN Connectors 6/11/2014