

AT-CUT CRYSTAL UNIT (SMD • Metal-can Type)

RoHS compliant

HCM49


1000pcs/reel




FEATURES

- Surface mount type of metal-can HC-49/U-S.
High performance with the resistance weld sealing.
- Suitable for various applications such as communication devices, AV devices and measuring instruments.

DIMENSION [mm]



SOLDER PAD LAYOUT [mm]



STANDARD SPECIFICATIONS

Item	Model	HCM49	Conditions
Nominal Frequency	f_0	3.5MHz~30.0MHz (Fundamental)	Need to contact us for the available frequency
		30.0MHz~50.0MHz (3rd Overtone)	
Frequency Tolerance	$\Delta f/f_0$	$\pm 30\text{ppm}$	at 25°C
Frequency Tolerance over Operating Temperature Range	$\Delta f/f_0$	below 6.0MHz: $\pm 50\text{ppm}$	-10°C ~ +60°C
		above 6.0MHz: $\pm 30\text{ppm}$	
Operating Temperature Range	T_{OPR}	-40°C ~ +85°C	
Storage Temperature Range	T_{STR}	-55°C ~ +125°C	
Motional (series) resistance	R_1	Refer to the following table	at 25°C
Load capacitance	C_L	Fundamental: 10.0pF ~ ∞ 3rd Overtone: 5.0pF ~ ∞	Need to specify your requirement
Shunt capacitance	C_0	7.0pF Max.	
Level of drive	D_L	100 μW	
Insulation Resistance	I_R	500M Ω Min.	DC100V $\pm 15\text{V}$
Aging (first year)	$\Delta f/f_0$	$\pm 5\text{ppm}$ Max.	25°C $\pm 3^\circ\text{C}$

MOTIONAL (SERIES) RESISTANCE (R_1)

Frequency Range	$3.5\text{MHz} \leq f_0 < 4.0\text{MHz}$	$4.0\text{MHz} \leq f_0 < 6.0\text{MHz}$	$6.0\text{MHz} \leq f_0 < 10\text{MHz}$	$10\text{MHz} \leq f_0 < 14\text{MHz}$	$14\text{MHz} \leq f_0 < 30\text{MHz}$	$30\text{MHz} \leq f_0 < 36\text{MHz}$	$36\text{MHz} \leq f_0 \leq 50\text{MHz}$
Mode	Fundamental	Fundamental	Fundamental	Fundamental	Fundamental	3rd Overtone	3rd Overtone
R_1	200 Ω Max.	150 Ω Max.	100 Ω Max.	80 Ω Max.	50 Ω Max.	140 Ω Max.	100 Ω Max.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Citizen:

[HCM49-28.224MABJTR](#) [HCM49-16.684MABJ-UT](#) [HCM49-18.000MABJTR](#) [HCM49-14.7456MABJTR](#) [HCM49-16.000MAMJTR](#) [HCM49-49.152MABJTR](#) [HCM49-6.764375MAMITR](#) [HCM49-48.000MABJTR](#) [HCM49-11.0592MBGKTR](#) [HCM49-6.000MABJTR](#) [HCM49-6.000MANITR](#) [HCM49-4.194304MBBJTR](#) [HCM49-24.576MABJTR](#) [HCM49-5.5296MABJTR](#) [HCM49-6.144MBBITR](#) [HCM49-3.579545MABKTR](#) [HCM49-50.000MABJTR](#) [HCM49-8.000MABJTR](#) [HCM49-4.433619MABJTR](#) [HCM49-9.8304MBBJTR](#) [HCM49-14.31818MABJTR](#) [HCM49-3.579545MABJTR](#) [HCM49-40.000MABJTR](#) [HCM49-24.000MBBITR](#) [HCM49-5.000MABJTR](#) [HCM49-12.288MABJTR](#) [HCM49-18.432MABJTR](#) [HCM49-24.000MABJTR](#) [HCM49-14.31818MABKTR](#) [HCM49-12.000MABJTR](#) [HCM49-12.000MBBKTR](#) [HCM49-3.6864MABJTR](#) [HCM49-10.000MABJTR](#) [HCM49-4.194304MABJTR](#) [HCM49-14.31818MAAKTR](#) [HCM49-9.000MABJTR](#) [HCM49-16.000MABJTR](#) [HCM49-9.8304MABJTR](#) [HCM49-10.240MABJTR](#) [HCM49-16.257MABJTR](#) [HCM49-16.384MABJTR](#) [HCM49-4.9152MABJTR](#) [HCM49-15.000MABJTR](#) [HCM49-16.000MBBITR](#) [HCM49-20.000MABJTR](#) [HCM49-11.0592MABJTR](#) [HCM49-7.3728MABJTR](#) [HCM49-19.6608MABJTR](#) [HCM49-15.360MABJTR](#) [HCM49-4.000MABJTR](#) [HCM49-16.2570MABJTR](#) [HCM49-17.734475MABJTR](#) [HCM49-27.000MABJTR](#) [HCM49-32.000MABJTR](#) [HCM49-4.096MABJTR](#) [HCM49-25.000MABJTR](#)