

## FO connectors - VS-PPC-C1-SCRJ-MNNA-PG9-A4D-C - 1608032

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid  
(<http://phoenixcontact.com/download>)



Fiber optic connector SC-RJ, IP67, with push-pull interlocking, metal housing, duplex, with fast connection technology, for polymer fiber 980/1000 µm, for individual wire diameter 2.2 mm, for cable cross section 6.5 mm ... 9.5 mm



### Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	71.0 g
Custom tariff number	85366990
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Number of positions	2
Connection profile	SCRJ in acc. with IEC 61754-24
Locking type	Push Pull
Fiber type	Polymer fiber
Ferrule diameter	2.50 mm
Insertion/withdrawal cycles	≥ 500
External cable diameter	6.5 mm ... 9.5 mm
Color	silver

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Degree of protection	IP67

#### Material data

Flammability rating according to UL 94	V0
Housing material	Zinc die-cast

## FO connectors - VS-PPC-C1-SCRJ-MNNA-PG9-A4D-C - 1608032

### Technical data

#### Material data

Housing surface material	Nickel-plated
Material	Metal
O-ring material	NBR
Cable seal material	TPE
Material housing intermediate seal	NBR
Ferrule material	Copper alloy
Ferrule holder color	blue

#### Electrical characteristics

Number of positions	2
Degree of pollution	2
Attenuation	≤ 1.5 dB (Insertion attenuation)

#### Standards and Regulations

Standards/regulations	IEC PAS 61076-3-117
Flammability rating according to UL 94	V0

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	19170122
eCl@ss 9.0	19170122

#### ETIM

ETIM 3.0	EC001122
ETIM 4.0	EC001122
ETIM 5.0	EC001122

#### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501

## FO connectors - VS-PPC-C1-SCRJ-MNNA-PG9-A4D-C - 1608032

### Classifications

#### UNSPSC

UNSPSC 13.2	31261501
-------------	----------

### Approvals

#### Approvals

#### Approvals

UL Listed / EAC / EAC / EAC

#### Ex Approvals

#### Approvals submitted

### Approval details

UL Listed 
---

EAC
-----

EAC
-----

EAC
-----

### Accessories

#### Accessories

#### Assembly tool

Tool set - TF-SCRJ-POF KONF SET - 1405246



SC-RJ cutting tool set, for polymer fiber, for field assembly of SC-RJ/IP20 and SC-RJ/IP67 push/pull connectors with fast connection technology, consisting of stripping tool, aramid scissors, SC-RJ cutting tool, microscope

## FO connectors - VS-PPC-C1-SCRJ-MNNA-PG9-A4D-C - 1608032

### Accessories

---


#### FO accessories - VS-SCRJ-POF-KONFTOOL-POLISH - 1658820



SC-RJ polishing tool set, for polymer fiber, for field assembly of the SC-RJ connector (IP20/IP67) with fast connection technology, with stripping tool, diagonal cutter, aramid scissors, polishing materials, microscope, 2x SC-RJ connector IP20

---

#### FO accessories - VS-SCRJ-POF-POLISH - 1656673



Refilling set for VS-SC-RJ-POF-KONFTOOL-POLISH, consisting of two polishing discs and a polisher

---

#### FO accessories - CUTFOX-SCRJ-POF - 1405247



SC-RJ cutting tool, for polymer fiber, for field assembly of SC-RJ/IP20 and SC-RJ/IP67 push/pull connectors with fast connection technology

---

#### FO accessories - WIREFOX-PN POF - 1405249




Sheath stripping tool, for polymer fiber

---


### Drawings

## FO connectors - VS-PPC-C1-SCRJ-MNNA-PG9-A4D-C - 1608032

Schematic diagram



Dimensional drawing



Push-Pull SC-RJ connector IP65/67

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

1608032